

# MABAC Method for Multiple Attribute Group Decision Making under Single-Valued Neutrosophic Sets and Applications to Performance Evaluation of Sustainable Microfinance Groups Lending

--Manuscript Draft--

|   |   |
|---|---|
| <b>Manuscript Number:</b>   | PONE-D-22-32075R1   |
| <b>Article Type:</b>  | Research Article  |
| <b>Full Title:</b>  | MABAC Method for Multiple Attribute Group Decision Making under Single-Valued Neutrosophic Sets and Applications to Performance Evaluation of Sustainable Microfinance Groups Lending   |
| <b>Short Title:</b>   | MABAC Method for Multiple Attribute Group Decision Making with SVNNS  |
| <b>Corresponding Author:</b>  | Hui Ran<br>Liuzhou Vocational and Technical College<br>Liuzhou, CHINA   |
| <b>Keywords:</b>  | MAGDM; single-valued neutrosophic sets (SVNSs); MABAC method; MDM; performance evaluation; microfinance groups lending  |
| <b>Abstract:</b>  | As an important supplement to my country's financial institutions, micro-loan companies serve "agriculture, rural areas and farmers", small and micro enterprises, and individuals, to a certain extent, alleviating the financing difficulties of such groups and regulating private finance. However, micro-loan companies only lend but do not deposit. In the process of lending, due to inadequate risk management, the risk problem has become increasingly prominent. With the continuous growth of the loan amount of rural credit and the continuous increase of microfinance groups lending customers, it faces certain problems in its risk management, which increases the risks of the company in all aspects. The performance evaluation of sustainable microfinance groups lending is a classical MAGDM issues. In such paper, the Hamming distances of single-valued neutrosophic sets (SVNSs) and maximizing deviation method (MDM) is used to obtain the attribute weights and the single-valued neutrosophic numbers MABAC(SVNN-MABAC) method is structured for MAGDM under SVNNS. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVNN-MABAC. |
| <b>Order of Authors:</b>  | Hui Ran   |
| <b>Response to Reviewers:</b>   | We are very thankful for these valuable comments given by the referees. The main changes are the attached file.   |
| <b>Additional Information:</b>  |   |
| <b>Question</b>   | <b>Response</b>   |
| <b>Financial Disclosure</b><br><br>Enter a financial disclosure statement that describes the sources of funding for the work included in this submission. Review the <a href="#">submission guidelines</a> for detailed requirements. View published research articles from <a href="#">PLOS ONE</a> for specific examples.<br><br>This statement is required for submission and <b>will appear in the published article</b> if the submission is accepted. Please make | The author(s) received no specific funding for this work.   |

sure it is accurate.

#### Unfunded studies

Enter: *The author(s) received no specific funding for this work.*

#### Funded studies

Enter a statement with the following details:

- Initials of the authors who received each award
- Grant numbers awarded to each author
- The full name of each funder
- URL of each funder website
- Did the sponsors or funders play any role in the study design, data collection and analysis, decision to publish, or preparation of the manuscript?
- **NO** - Include this sentence at the end of your statement: *The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.*
- **YES** - Specify the role(s) played.

\* typeset

#### Competing Interests

Use the instructions below to enter a competing interest statement for this submission. On behalf of all authors, disclose any [competing interests](#) that could be perceived to bias this work—acknowledging all financial support and any other relevant financial or non-financial competing interests.

This statement is **required** for submission and **will appear in the published article** if the submission is accepted. Please make sure it is accurate and that any funding sources listed in your Funding Information later in the submission form are also declared in your Financial Disclosure statement.

View published research articles from [PLOS ONE](#) for specific examples.

The authors have declared that no competing interests exist.

#### NO authors have competing interests

Enter: *The authors have declared that no competing interests exist.*

#### Authors with competing interests

Enter competing interest details beginning with this statement:

*I have read the journal's policy and the authors of this manuscript have the following competing interests: [insert competing interests here]*

\* typeset

#### Ethics Statement

N/A

Enter an ethics statement for this submission. This statement is required if the study involved:

- Human participants
- Human specimens or tissue
- Vertebrate animals or cephalopods
- Vertebrate embryos or tissues
- Field research

Write "N/A" if the submission does not require an ethics statement.

General guidance is provided below.

Consult the [submission guidelines](#) for detailed instructions. **Make sure that all information entered here is included in the Methods section of the manuscript.**

## Format for specific study types

### Human Subject Research (involving human participants and/or tissue)

- Give the name of the institutional review board or ethics committee that approved the study
- Include the approval number and/or a statement indicating approval of this research
- Indicate the form of consent obtained (written/oral) or the reason that consent was not obtained (e.g. the data were analyzed anonymously)

### Animal Research (involving vertebrate animals, embryos or tissues)

- Provide the name of the Institutional Animal Care and Use Committee (IACUC) or other relevant ethics board that reviewed the study protocol, and indicate whether they approved this research or granted a formal waiver of ethical approval
- Include an approval number if one was obtained
- If the study involved *non-human primates*, add *additional details* about animal welfare and steps taken to ameliorate suffering
- If anesthesia, euthanasia, or any kind of animal sacrifice is part of the study, include briefly which substances and/or methods were applied

### Field Research

Include the following details if this study involves the collection of plant, animal, or other materials from a natural setting:

- Field permit number
- Name of the institution or relevant body that granted permission

### Data Availability

Authors are required to make all data underlying the findings described fully available, without restriction, and from the time of publication. PLOS allows rare exceptions to address legal and ethical concerns. See the [PLOS Data Policy](#) and [FAQ](#) for detailed information.

Yes - all data are fully available without restriction

A Data Availability Statement describing where the data can be found is required at submission. Your answers to this question constitute the Data Availability Statement and **will be published in the article**, if accepted.

**Important:** Stating 'data available on request from the author' is not sufficient. If your data are only available upon request, select 'No' for the first question and explain your exceptional situation in the text box.

Do the authors confirm that all data underlying the findings described in their manuscript are fully available without restriction?

**Describe where the data may be found in full sentences. If you are copying our sample text, replace any instances of XXX with the appropriate details.**

- If the data are **held or will be held in a public repository**, include URLs, accession numbers or DOIs. If this information will only be available after acceptance, indicate this by ticking the box below. For example: *All XXX files are available from the XXX database (accession number(s) XXX, XXX).*
- If the data are all contained **within the manuscript and/or Supporting Information files**, enter the following:  
*All relevant data are within the manuscript and its Supporting Information files.*
- If neither of these applies but you are able to provide **details of access elsewhere**, with or without limitations, please do so. For example:

*Data cannot be shared publicly because of [XXX]. Data are available from the XXX Institutional Data Access / Ethics Committee (contact via XXX) for researchers who meet the criteria for access to confidential data.*

*The data underlying the results presented in the study are available from (include the name of the third party*

The data used to support the findings of this study are included within the article.

|   |  |
|---|--|
| <p><i>and contact information or URL).</i></p> <ul style="list-style-type: none"><li>• This text is appropriate if the data are owned by a third party and authors do not have permission to share the data.</li></ul> <p>* typeset</p> |  |
| Additional data availability information:   |  |

---

# MABAC Method for Multiple Attribute Group Decision Making under Single-Valued Neutrosophic Sets and Applications to Performance Evaluation of Sustainable Microfinance Groups Lending

**Hui Ran**

College of Finance and Logistics Management, LiuZhou Vocational & Technical College, Liuzhou, 545006, Guangxi, China

\*Corresponding author, E-mail: ranhui0808@163.com

**Abstract:** As an important supplement to my country's financial institutions, micro-loan companies serve "agriculture, rural areas and farmers", small and micro enterprises, and individuals, to a certain extent, alleviating the financing difficulties of such groups and regulating private finance. However, micro-loan companies only lend but do not deposit. In the process of lending, due to inadequate risk management, the risk problem has become increasingly prominent. With the continuous growth of the loan amount of rural credit and the continuous increase of microfinance groups lending customers, it faces certain problems in its risk management, which increases the risks of the company in all aspects. The performance evaluation of sustainable microfinance groups lending is a classical MAGDM issues. In such paper, the Hamming distances of single-valued neutrosophic sets (SVNSs) and maximizing deviation method (MDM) is used to obtain the attribute weights and the single-valued neutrosophic numbers MABAC(SVNN-MABAC) method is structured for MAGDM under SVNSs. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVNN-MABAC.

**Keywords:** MAGDM; single-valued neutrosophic sets (SVNSs); MABAC method; MDM; performance evaluation; microfinance groups lending

---

## 1. Introduction

The MADM is a kind of very complex optimization decision-making problem, which often occurs in the field of decision engineering, economics, military, and public management[1-5]. In the process of MADM, the value of decision-making attributes often has information uncertainty, and the data is difficult to estimate, predict, and evaluate[6-13]. This is more general than the decision attribute value is accurate data and clear information. Decision problems have multiple decision attributes[14-17]. For qualitative decision attributes, the decision attribute values are usually presented in the form of language evaluation, such as excellent, good, qualified, unqualified and other semantic information, which brings difficulties to mathematical calculation and analysis, simply quantitative conversion of semantic information, such as setting grades, cannot guarantee scientificity, and it is easy to lose important information, resulting in decision-making mistakes[18-22]. Zadeh [23] structured the fuzzy sets (FSs). Then, Atanassov [24] structured defined intuitionistic fuzzy sets (IFs). Liu et al. [25] defined the Dombi BM operations for MAGDM. Smarandache [26] structured the neutrosophic sets (NSs). However, considering that the medium intelligence set is defined in a non-standard sub interval, which is not convenient for application in engineering and natural science, Wang et al. [27] proposed the SVNNSs to solve this problem. It is a subclass of the medium intelligence set. It uses true membership, false membership and uncertainty functions to describe decision information together, which can be easily applied in engineering, science and other fields. SVNNSs have many obvious advantages in dealing with uncertain and fuzzy decision information, and a lot of research has been done on this. Biswas, Pramanik and Giri [28] used SVNNSs to represent decision information and TOPSIS to propose MADM method. Jiang and Shou [29] proposed the similarity measurement for SVNNSs based on Dempster Shafer distance theory. Ye [30] proposed a decision weighted correlation coefficient of SVNNSs, and proposed a MADM with cross entropy of SVNNSs. The key roles of TOPSIS [31] is that the distance between the optimal scheme and the positive ideal scheme should be the shortest, and the distance between the optimal scheme and the negative ideal scheme should be the farthest. The combination of TOPSIS method [32-37] and SVNNSs [38-49] can effectively solve the MADM problem [50-59].

There are three shortcomings in disposing of the MAGDM problems under SVNNSs environment that to form our incentives in the following:

(1) The existing decision methods have complex computation degree [38-49]. How to investigate the decision methods consider the relatively simpler computation degree is an interesting and hot topic. For this reason, the first incentive of this paper is to build the new relatively simpler decision methods.



(2) The existing weight methods just consider completely known weight information[32-37]. How to investigate the weight consider completely unknown weight is an interesting and hot topic. For this reason, the second incentive of this paper is to design the new weight method, which can deal with completely unknown weight.

(3) The timely innovation of group lending technology of microfinance is important for promoting the innovation of financial support for agricultural products in the implementation of China's rural revitalization strategy[60-65]. It is of practical value and theoretical significance to promote the innovation of financial support for agricultural products in the implementation of China's rural revitalization strategy and to bridge the theoretical controversy of microcredit loan technology. The performance evaluation of sustainable microfinance groups lending in Chinese is still in a blank state. Therefore, it is urgent for researchers in related disciplines to conduct exploratory research in this field to enrich the research content of performance evaluation of sustainable microfinance groups lending in my country. The performance evaluation of sustainable microfinance groups lending is a classical MAGDM issues. Thus, the third incentive of this paper is to build new decision methods for performance evaluation of sustainable microfinance groups lending.

On this basis, combined with the characteristics of performance evaluation of sustainable microfinance groups lending, a new MAGDM method for performance evaluation of sustainable microfinance groups lending in SVNNs environment is proposed. Specific research points are listed as follows:

(1) In this paper, the SVNN-MABAC method is built based on the MABAC [66] and SVNNs with completely unknown weight information. The SVNN-MABAC investigate the decision methods consider the distances-based measures degree.

(2) For deriving the completely known weight of the attribute, an optimization model is built on the MDM method, by which the attribute weights can be decided. Then, the optimal alternative is chosen through calculating the maximizing deviation among different alternatives. Then, combine the traditional MABAC model with SVNNs information, the SVNN-MABAC method is established and the computing steps for MAGDM are built.

(3) The main advantages of the SVNN-MABAC method are given as follows: the computing results by SVNN-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains

and losses into account; it is available to combine this model with other approaches. Hence, the SVN-MABAC method is a good tool to derive reasonable decision-making results.

(4) Finally, a numerical example for performance evaluation of sustainable microfinance groups lending has been given and some comparisons is used to illustrate advantages of SVN-MABAC. This paper mainly provides method guidance and technical support for the realization of SVN-MABAC. This has far-reaching significance for the decision-making of sustainable microfinance groups lending in the public sector, infrastructure construction and even national security and stability.

In order to do, the reminder of our paper proceeds. The SVN is reviewed in Sec. 2. The SVN-MABAC method for MAGDM is defined in Sec. 3. An example for performance evaluation of sustainable microfinance groups lending is given to show the superiority in Sec. 4. the conclusion is fully given in Sec. 5.

## 2. Preliminaries

Wang et al. [27] defined the given SVN

**Definition 1** [27]. The SVN  $A$  in  $Y$  is defined:

$$YA = \{(y, AT(y), AI(y), AF(y)) | y \in Y\} \quad (1)$$

with defined truth-membership  $AT(y)$ , defined indeterminacy-membership  $AI(y)$  and defined falsity-membership  $AF(y)$ ,  $AT(y), AI(y), AF(y) \in [0, 1]$ ,  $0 \leq AT(y) + AI(y) + AF(y) \leq 3$ .

The SVN is expressed as  $YA = (AT, AI, AF)$ ,  $AT, AI, AF \in [0, 1]$ ,  $0 \leq AT + AI + AF \leq 3$ .

**Definition 2** [67]. Let  $YA = (AT, AI, AF)$  be the SVN, the score value is:

$$SV(YA) = \frac{(2 + AT - AI - AF)}{3}, \quad SV(YA) \in [0, 1]. \quad (2)$$

**Definition 3** [67]. Let  $YA = (AT, AI, AF)$  be the SVN, the accuracy value is:

$$HV(YA) = AT - AF, \quad HV(YA) \in [-1, 1]. \quad (3)$$

Peng et al. [67] came up with order decision relation for SVN.

**Definition 4** [67]. Let  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$  be two given SVN, let

$$SV(YA) = \frac{(2 + AT - AI - AF)}{3} \quad \text{and} \quad SV(YB) = \frac{(2 + BT - BI - BF)}{3}, \quad \text{and} \quad \text{let}$$

$HV(YA) = AT - AF$  and  $HV(YB) = BT_B - BF$ , if  $SV(YA) < SV(YB)$ ,  $YA < YB$ ; if  $SV(YA) = SV(YB)$ , then (1) if  $HV(YA) = HV(YB)$ ,  $YA = YB$ ; (2) if  $HV(YA) < HV(YB)$ ,  $YA < YB$ .

**Definition 5[68].** Let  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$  be two SVNNS, the basic operations are defined:

- (1)  $YA \oplus YB = (AT + BT - AT \cdot BT, AI + BI - AI \cdot BI, AF + BF - AF \cdot BF)$ ;
- (2)  $YA \otimes YB = (AT \cdot BT, AI + BI - AI \cdot BI, AF + BF - AF \cdot BF)$ ;
- (3)  $\lambda YA = (1 - (1 - AT)^\lambda, (AI)^\lambda, (AF)^\lambda), \lambda > 0$ ;
- (4)  $(YA)^\lambda = ((AT)^\lambda, (AI)^\lambda, 1 - (1 - AF)^\lambda), \lambda > 0$ .

**Definition 6[69].** Let  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$ , then the Hamming distance between  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$  is defined:

$$HD(YA, YB) = \frac{|AT - BT| + |AI - BI| + |AF - BF|}{3} \quad (4)$$

### 3. The MABAC method for MAGDM with SVNNS

Let  $ZZ = \{ZZ_1, ZZ_2, \dots, ZZ_n\}$  be the set of attributes,  $WZ = \{WZ_1, WZ_2, \dots, WZ_n\}$  be the weight of attributes  $ZZ_j$ . Let  $PP = \{PP_1, PP_2, \dots, PP_m\}$  be alternatives. And  $AQ = (aq_{ij})_{m \times n} = (AT_{ij}, AI_{ij}, AF_{ij})_{m \times n}$  is the SVN matrix. Integrating the MABAC method for MAGDM with SVNNS, we build the SVN-MABAC method with SVNNS. The SVN-MABAC procedures can be described subsequently.

**Step 1.** Set up the SVN matrix  $AQ = (aq_{ij})_{m \times n} = (AT_{ij}, AI_{ij}, AF_{ij})_{m \times n}$ .

$$AQ = (aq_{ij})_{m \times n} = \begin{bmatrix} aq_{11} & aq_{12} & \dots & aq_{1n} \\ aq_{21} & aq_{22} & \dots & aq_{2n} \\ \vdots & \vdots & \vdots & \vdots \\ aq_{m1} & aq_{m2} & \dots & aq_{mn} \end{bmatrix} \quad (6)$$

**Step 2.** Normalize matrix  $AQ = (aq_{ij})_{m \times n}$  to  $NQ = [nq_{ij}]_{m \times n}$ .

$$\begin{aligned}
 nq_{ij} &= (NT_{ij}, NI_{ij}, NF_{ij}) \\
 &= \begin{cases} (AT_{ij}, AI_{ij}, AF_{ij}), & ZZ_j \text{ is a benefit criterion} \\ (AF_{ij}, AI_{ij}, AT_{ij}), & ZZ_j \text{ is a cost criterion} \end{cases}
 \end{aligned} \tag{8}$$

**Step 3.** Utilize the MDM to determine the weight of attributes.

The MDM [70] is used to derive the weight values.

(1) Depending on the  $NQ = [nq_{ij}]_{m \times n}$ , the deviation of  $PP_i$  from other alternatives is calculated.

$$SVNNHD_{ij} = \sum_{t=1}^m w_{z_j} \cdot HD(nq_{ij}, nq_{tj}) \tag{9}$$

$$\text{where } HD(nq_{ij}, nq_{tj}) = \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3}.$$

(2) Calculate the weighted deviation.

$$\begin{aligned}
 SVNNHD_j(wz) &= \sum_{i=1}^m SVNNHD_{ij}(wz) \\
 &= \sum_{i=1}^m \sum_{t=1}^m w_{z_j} \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right)
 \end{aligned} \tag{10}$$

(3) Construct the programming model.

$$(M-1) \begin{cases} \max D(wz) = \sum_{j=1}^n \sum_{i=1}^m \sum_{t=1}^m w_{z_j} \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right) \\ s.t. \ w_{z_j} \geq 0, \sum_{j=1}^n w_{z_j}^2 = 1 \end{cases} \tag{11}$$

To solve this defined model, The Lagrange function is used to solve this model.

$$L(wz, \xi) = \sum_{j=1}^n \sum_{i=1}^m \sum_{t=1}^m w_{z_j} \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right) + \frac{\xi}{2} \left( \sum_{j=1}^n w_{z_j}^2 - 1 \right)$$

where  $\xi$  is the Lagrange decision multiplier, the partial derivatives are obtained.

$$\begin{cases} \frac{\partial L}{\partial w_{z_j}} = \sum_{i=1}^m \sum_{t=1}^m \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right) + \xi w_{z_j} = 0 \\ \frac{\partial L}{\partial \xi} = \frac{1}{2} \left( \sum_{j=1}^n w_{z_j}^2 - 1 \right) = 0 \end{cases}$$

And the weight information is obtained.

$$wz_j^* = \frac{\sum_{i=1}^m \sum_{t=1}^m |NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{\sqrt{\sum_{j=1}^n \left( \sum_{i=1}^m \sum_{t=1}^m (|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|) \right)^2}}$$

Finally, the normalized weights are obtained.

$$wz_j = \frac{\sum_{i=1}^m \sum_{t=1}^m (|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|)}{\sum_{j=1}^n \sum_{i=1}^m \sum_{t=1}^m (|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|)} \quad (12)$$

**Step 4.** Obtain the weighted matrix  $OQ = (oq_{ij})_{m \times n}$ :

$$\begin{aligned} oq_{ij} &= (WNT_{ij}, WNI_{ij}, WNF_{ij}) \\ &= wz_j \cdot nq_{ij} = \left( 1 - (1 - NT_{ij})^{wz_j}, (NI_{ij})^{wz_j}, (NF_{ij})^{wz_j} \right) \end{aligned} \quad (13)$$

**Step 5.** Obtain the defined SVNNBAA  $GQ = (gq_j)_{1 \times n}$ .

$$gq_j = \prod_{i=1}^m (oq_{ij})^{\frac{1}{m}} = \left( \prod_{i=1}^m (WNT_{ij})^{\frac{1}{m}}, \prod_{i=1}^m (WNI_{ij})^{\frac{1}{m}}, 1 - \prod_{i=1}^m (1 - WNF_{ij})^{\frac{1}{m}} \right) \quad (14)$$

**Step 6.** Obtain the SVN distance decision matrix  $DQ = (dq_{ij})_{m \times n}$  from SVNNBAA with Eq. (15).

$$dq_{ij} = \begin{cases} (HD(oq_{ij}, gq_j)), & \text{if } SV(oq_{ij}) \geq S(gq_j), \\ -HD(oq_{ij}, gq_j), & \text{if } SV(oq_{ij}) < S(gq_j), \end{cases} \quad (15)$$

**Step 7.** Obtain the final order value  $SVNNF_i$ .

$$SVNNF_i = \sum_{j=1}^n dq_{ij} \quad (16)$$

**Step 8.** The given alternatives can be order with  $SVNNF_i$ . The higher information value of  $SVNNF_i$  is, the optimal selection will be.

## 4. The Empirical Example and Comparative analysis

### 4.1 An empirical example

Microfinance is an institutionalized form of credit that provides credit services to the low-income poor. Starting from the mid-1970s, some developing countries in Asia and Latin America, recognizing the disadvantaged position of the poor in the formal financial market, borrowed some features of traditional private credit and modern management experience, combined with the economic and social conditions of the countries

where they are located and the economic and cultural characteristics of the poor, and on the basis of continuous exploration and experimentation, creatively constructed a variety of Credit systems and methods. Since most of the institutional arrangements of such credit modalities are aimed at the self-employed poor with normal production capacity, and they are designed to treat the self-employed poor households and the economic activities they are engaged in as micro-enterprises. Under these assumptions, this type of credit service for the poor is referred to as microenterprise credit or microcredit for short. When this approach was introduced in our country, it was translated as microcredit. The situation between Internet financial enterprises and traditional commercial banks is not a "zero-sum game". Compared with traditional financial service products, Internet financial wealth management products are more substitutable. In this context, subject to the gradually approaching market pressure of Internet finance, traditional commercial banks must actively carry out reforms and innovations if they want to calmly deal with and reverse the adversity. Therefore, commercial banks must change the traditional commercial banking business operation model of "sugar daddy, large households, relying on resources, and profit margins", and actively take measures to deal with the crises and challenges brought by Internet financial products. In recent years, the development momentum of my country's Internet finance has been particularly rapid. However, with the continuous decision improvement of the socialist market economic with Chinese characteristics, the industry environment for the development of my country's Internet finance has been gradually standardized, but at the same time, new problems have emerged. From the perspective of the development of microfinance business, Internet finance has spawned a wide variety of business products. However, due to the influence of factors such as lack of industry supervision, commercial banks' microfinance business risk events frequently occur, which is not conducive to commercial banks' sustainable operations. The performance evaluation of sustainable microfinance groups lending is the MAGDM. In this paper, an empirical application of performance evaluation of sustainable microfinance groups lending will be provided with SVNN-MABAC. There are five microfinance groups  $PP_i (i = 1, 2, 3, 4, 5)$  are to evaluated the performance of sustainable microfinance groups lending. In order to assess these microfinance groups fairly, the experts group give their assessment with four defined attributes: ①ZZ<sub>1</sub> is the pay back ability; ②ZZ<sub>2</sub> is the loan amount; ③ZZ<sub>3</sub> is the loan utilization rate; ④ZZ<sub>4</sub> is the loan repayment ability. Evidently, ZZ<sub>2</sub> is the cost, others are the benefit. Then, the SVNN-MABAC method is applied to MAGDM for solving the performance evaluation of

sustainable microfinance groups lending with SVNNs. The built SVNN-MABAC method involves the following steps:

**Step 1.** Set up the SVNN-matrix  $AQ = (aq_{ij})_{5 \times 4}$  as in Table 1.

**Table 1.** SVNN information

|                 | $ZZ_1$             | $ZZ_2$             | $ZZ_3$             | $ZZ_4$             |
|-----------------|--------------------|--------------------|--------------------|--------------------|
| PP <sub>1</sub> | (0.53, 0.35, 0.37) | (0.26, 0.25, 0.22) | (0.50, 0.35, 0.50) | (0.33, 0.33, 0.35) |
| PP <sub>2</sub> | (0.55, 0.25, 0.55) | (0.58, 0.53, 0.23) | (0.52, 0.07, 0.59) | (0.55, 0.23, 0.55) |
| PP <sub>3</sub> | (0.35, 0.07, 0.55) | (0.53, 0.32, 0.38) | (0.53, 0.07, 0.58) | (0.53, 0.29, 0.58) |
| PP <sub>4</sub> | (0.33, 0.33, 0.33) | (0.52, 0.02, 0.22) | (0.55, 0.53, 0.55) | (0.33, 0.33, 0.36) |
| PP <sub>5</sub> | (0.35, 0.09, 0.35) | (0.32, 0.05, 0.29) | (0.59, 0.35, 0.53) | (0.33, 0.33, 0.33) |

**Step 2.** Normalize  $AQ = (aq_{ij})_{5 \times 4}$  to  $NQ = [nq_{ij}]_{5 \times 4}$  (See Table 2).

**Table 2.** The normalized SVNN information

|                 | $ZZ_1$             | $ZZ_2$             | $ZZ_3$             | $ZZ_4$             |
|-----------------|--------------------|--------------------|--------------------|--------------------|
| PP <sub>1</sub> | (0.53, 0.35, 0.37) | (0.22, 0.25, 0.26) | (0.50, 0.35, 0.50) | (0.33, 0.33, 0.35) |
| PP <sub>2</sub> | (0.55, 0.25, 0.55) | (0.23, 0.53, 0.58) | (0.52, 0.07, 0.59) | (0.55, 0.23, 0.55) |
| PP <sub>3</sub> | (0.35, 0.07, 0.55) | (0.38, 0.32, 0.53) | (0.53, 0.07, 0.58) | (0.53, 0.29, 0.58) |
| PP <sub>4</sub> | (0.33, 0.33, 0.33) | (0.22, 0.02, 0.52) | (0.55, 0.53, 0.55) | (0.33, 0.33, 0.36) |
| PP <sub>5</sub> | (0.35, 0.09, 0.35) | (0.29, 0.05, 0.32) | (0.59, 0.35, 0.53) | (0.33, 0.33, 0.33) |

**Step 3.** Obtain the attribute weights in Table 3.

**Table 3.** The attributes weights

|        | $ZZ_1$ | $ZZ_2$ | $ZZ_3$ | $ZZ_4$ |
|--------|--------|--------|--------|--------|
| $wz_j$ | 0.2574 | 0.1898 | 0.2667 | 0.2861 |

**Step 4.** Obtain the weighted matrix  $OQ = (oq_{ij})_{m \times n}$  (Table 4).

**Table 4.** SVNN weighted normalized values

| $ZZ_1$ | $ZZ_2$ |
|--------|--------|
|--------|--------|

|                          |                           |
|--------------------------|---------------------------|
| (0.2266, 0.2078, 0.2624) | (0.2066, 0.2427, 0.2642)  |
| (0.2262, 0.2406, 0.4626) | (0.4404, 0.2246, 0.2468)  |
| (0.2242, 0.4224, 0.4644) | (0.4026, 0.2422, 0.4682)  |
| (0.4602, 0.2268, 0.2066) | (0.2400, 0.2422, 0.6200)  |
| (0.2422, 0.4268, 0.2462) | (0.2264, 0.4206, 0.2606)  |
| $ZZ_3$                   | $ZZ_4$                    |
| (0.4622, 0.4266, 0.4084) | (0.4664, 0.2487, 0.2222)  |
| (0.2244, 0.4264, 0.4442) | (0.2424, 0.2267, 0.4468)  |
| (0.2622, 0.002, 0.2422)  | (0.2624, 0.2442, 0.2426)  |
| (0.2226, 0.2008, 0.2622) | (0.2224, 0.28607, 0.2266) |
| (0.2242, 0.4244, 0.4666) | (0.2020, 0.2067, 0.4660)  |

**Step 5.** Determine the SVNNBAA (Table 5).

**Table 5. SVNNBAA**

| SVNNBAA |                          |
|---------|--------------------------|
| $ZZ_1$  | (0.3322, 0.2362, 0.2223) |
| $ZZ_2$  | (0.3633, 0.003, 0.3233)  |
| $ZZ_3$  | (0.3336, 0.3006, 0.3633) |
| $ZZ_4$  | (0.2633, 0.2366, 0.2062) |

**Step 6.** Calculate the  $DQ = (dq_{ij})_{5 \times 4}$  (Table 5).

**Table 5. Distance matrix**

|                 | $ZZ_1$  | $ZZ_2$  | $ZZ_3$ | $ZZ_4$  |
|-----------------|---------|---------|--------|---------|
| PP <sub>1</sub> | -0.0837 | 0.0255  | 0.0400 | -0.1022 |
| PP <sub>2</sub> | 0.1320  | -0.0690 | 0.1297 | -0.1421 |



|                 |         |         |         |         |
|-----------------|---------|---------|---------|---------|
| PP <sub>3</sub> | -0.1054 | -0.0461 | -0.1078 | -0.1162 |
| PP <sub>4</sub> | -0.0480 | -0.0387 | -0.0293 | -0.1063 |
| PP <sub>5</sub> | -0.1227 | -0.0648 | -0.1418 | -0.2150 |

**Step 7.** Calculate  $SVNNF_i$  in Table 6.

**Table 6. The SVNNF values**

| Alternative     | SVNNF value |
|-----------------|-------------|
| PP <sub>1</sub> | -0.1204     |
| PP <sub>2</sub> | 0.0506      |
| PP <sub>3</sub> | -0.3755     |
| PP <sub>4</sub> | -0.2223     |
| PP <sub>5</sub> | -0.5443     |

**Step 8.** From the Table 6, the order is:  $PP_2 > PP_1 > PP_4 > PP_3 > PP_5$  and  $PP_2$  is the optimal selection.

#### 4.2 Compare analysis

The SVNN-MABAC is made comparison with SVNNWA & SVNNWG operators[67], SVNN-CODAS method[71] and SVNN-EDAS method[72]. The decision results of different methods are in Table7.

**Table 7. Results for different given methods**

| Methods         | Order                              | The optimal choice | The worst choice |
|-----------------|------------------------------------|--------------------|------------------|
| SVNNWA [67]     | $PP_2 > PP_4 > PP_5 > PP_1 > PP_3$ | $PP_2$             | $PP_3$           |
| SVNNWG [67]     | $PP_2 > PP_4 > PP_1 > PP_5 > PP_3$ | $PP_2$             | $PP_3$           |
| SVNN-CODAS [71] | $PP_2 > PP_1 > PP_4 > PP_5 > PP_3$ | $PP_2$             | $PP_3$           |

|                   |                                    |        |        |
|-------------------|------------------------------------|--------|--------|
| SVNN-EDAS [72]    | $PP_2 > PP_5 > PP_4 > PP_1 > PP_3$ | $PP_2$ | $PP_3$ |
| SVNN-MABAC method | $PP_2 > PP_1 > PP_4 > PP_3 > PP_5$ | $PP_2$ | $PP_3$ |

From Table 7, obviously, the best enterprise given is  $PP_2$  in the five given methods, and the worst selection is  $PP_3$  in most cases. In other words, the order of these five methods have light difference. Different decision methods may effectively solve the MAGDM problem from different research decision angles. These five given models have their given advantages: (1) the SVNNWA operator emphasis group decision influences; (2) the SVNNWG operator emphasis individual decision influences; (3) In the SVNN-CODAS method, the overall performance of the alternatives is measured by Euclidean distance and Hamming distance of negative ideal points, where Euclidean distance is used as the main measure for evaluation. If the Euclidean distance between two alternatives is very close, then the Hamming distance is used to compare the two alternatives. Among them, the closeness of the Euclidean distance can be determined by using the threshold parameter; (4) The SVNN-EDAS method has required fewer computations, although it results in the same ranking of alternatives. The evaluations of alternatives in EDAS method based on distance measures from the average solutions in terms of each criterion unlike TOPSIS and VIKOR. (5) The SVNN-MABAC method has a large amount of precious characteristic, such as: the computing results by SVNN-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains and losses into account; it is available to combine this model with other approaches. Hence, the SVNN-MABAC method is a good tool to derive reasonable decision making results.

## 5. Conclusion

In recent years, the development of Internet finance has shown an unprecedented prosperous trend, which is the result of the rapid decision development of Internet information technology and cloud technology. Under this background, there are endless cases of innovation and entrepreneurship in the domestic Internet finance field, especially the development of Internet wealth management products. Especially quickly. In 2014, Alibaba Finance launched the "Yue Bao" service for the first time, mainly providing Alipay wealth management services. This product is a wealth management fund product jointly launched by Alipay and Tianhong Fund. Money market financial instruments with high security and stability, such as certificates of deposit. Once the Yu'e Bao product was launched, it aroused strong reactions in the financial investment market. It is known as a "wealth management artifact" due to its low threshold and fast receipt of income. Under this wave, other Internet

financial companies have followed closely and launched various wealth management products, such as Baidu's "Baifa", Suning's "Change Money", Tencent's "Wealth Management", etc. Financial markets are showing unprecedented prosperity. The performance evaluation of sustainable microfinance groups lending is the MAGDM. In this given paper, the MABAC method is built for SVNN-MAGDM. First, the Hamming distances of SVNSs and MDM is employed to obtain the decision weights and the SVNN-MABAC method is structured for MAGDM under SVNSs. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to prove the SVNN-MABAC. The main contributions of this work are (1) The attribute weights are obtained by MDM method; (2) the paper constructs the SVNN-MABAC method for performance evaluation of sustainable microfinance groups lending; (3) the established method is illustrated by a case study for performance evaluation of sustainable microfinance groups lending; and (4) some comparisons prove the rationality and advantages.

According to the current research status in this field, research of evaluation methods will be continued in the following aspects in the future. (1) Consensus and consistency improvement should be investigated in group decision-making [73–79] for performance evaluation of sustainable microfinance groups lending. (2) The methods proposed in this paper is improved to consider the expression of evaluation information based on SVNSs, such as group decision method based on probabilistic linguistic information [80, 81] and probabilistic uncertain linguistic information [82, 83], which is also a topic worthy of future research.

## References

- [1] M. Akram, S. Naz, F. Smarandache, Generalization of Maximizing Deviation and TOPSIS Method for MADM in Simplified Neutrosophic Hesitant Fuzzy Environment, *Symmetry-Basel*, 11 (2019).
- [2] M. Akram, Shumaiza, F. Smarandache, Decision-Making with Bipolar Neutrosophic TOPSIS and Bipolar Neutrosophic ELECTRE-I, *Axioms*, 7 (2018).
- [3] M. Akram, Z. Niaz, F. Feng, Extended CODAS method for multi-attribute group decision-making based on 2-tuple linguistic Fermatean fuzzy Hamacher aggregation operators, *Granular Computing*, (2022) <https://doi.org/10.1007/s41066-41022-00332-41063>.
- [4] M. Akram, S. Naz, F. Feng, A. Shafiq, Assessment of hydropower plants in Pakistan: Muirhead mean-based 2-tuple linguistic t-spherical fuzzy model combining SWARA with COPRAS, *Arabian Journal for Science Engineering*, (2022) <https://doi.org/10.1007/s13369-13022-07081-13360>.
- [5] M. Akram, Z. Niaz, 2-Tuple linguistic Fermatean fuzzy decision-making method based on COCOSO with CRITIC for drip irrigation system analysis, *Journal of Computational Cognitive Engineering*, (2022) <https://doi.org/10.47852/bonviewJCCE2202356>.
- [6] S.A. Edalatpanah, Neutrosophic structured element, *Expert Systems*, 37 (2020) 17.
- [7] H. Eroglu, R. Sahin, A Neutrosophic VIKOR Method-Based Decision-Making with an Improved Distance

- 
- Measure and Score Function: Case Study of Selection for Renewable Energy Alternatives, *Cognitive Computation*, 12 (2020) 1338-1355.
- [8] Y.M. Gong, Z.Y. Ma, M.J. Wang, X.Y. Deng, W. Jiang, A New Multi-Sensor Fusion Target Recognition Method Based on Complementarity Analysis and Neutrosophic Set, *Symmetry-Basel*, 12 (2020) 18.
- [9] M.R. Hashmi, M. Riaz, F. Smarandache, m-polar Neutrosophic Generalized Weighted and m-polar Neutrosophic Generalized Einstein Weighted Aggregation Operators to Diagnose Coronavirus (COVID-19), *Journal of Intelligent & Fuzzy Systems*, 39 (2020) 7381-7401.
- [10] A.M. Khalil, D.Q. Cao, A. Azzam, F. Smarandache, W.R. Alharbi, Combination of the Single-Valued Neutrosophic Fuzzy Set and the Soft Set with Applications in Decision-Making, *Symmetry-Basel*, 12 (2020) 17.
- [11] B. Ning, G. Wei, R. Lin, Y. Guo, A novel MADM technique based on extended power generalized Maclaurin symmetric mean operators under probabilistic dual hesitant fuzzy setting and its application to sustainable suppliers selection, *Expert Systems with Applications*, 204 (2022) 117419.
- [12] S. Wang, G. Wei, J. Lu, J. Wu, C. Wei, X. Chen, GRP and CRITIC method for probabilistic uncertain linguistic MAGDM and its application to site selection of hospital constructions, *Soft Computing*, 26 (2022) 237–251.
- [13] M. Zhao, H. Gao, G. Wei, C. Wei, Y. Guo, Model for network security service provider selection with probabilistic uncertain linguistic TODIM method based on prospect theory, *Technological and Economic Development of Economy*, 28 (2022) 638–654.
- [14] H.P. Ren, H.H. Chen, W. Fei, D.F. Li, A MAGDM Method Considering the Amount and Reliability Information of Interval-Valued Intuitionistic Fuzzy Sets, *International Journal of Fuzzy Systems*, 19 (2017) 715-725.
- [15] M.R. Feylizadeh, A. Mahmoudi, M. Bagherpour, D.F. Li, Project crashing using a fuzzy multi-objective model considering time, cost, quality and risk under fast tracking technique: A case study, *Journal of Intelligent & Fuzzy Systems*, 35 (2018) 3615-3633.
- [16] D.F. Li, Y.T. Wang, A. Madden, Y. Ding, J. Tang, G.G. Sun, N. Zhang, E.G. Zhou, Analyzing stock market trends using social media user moods and social influence, *Journal of the Association for Information Science and Technology*, 70 (2019) 1000-1013.
- [17] X.Y. Xiong, P. Zhou, Y.Q. Yin, T.C.E. Cheng, D.F. Li, An exact branch-and-price algorithm for multitasking
-

- 
- scheduling on unrelated parallel machines, *Naval Research Logistics*, 66 (2019) 502-516.
- [18] N.T. Thong, L.Q. Dat, L.H. Son, N.D. Hoa, M. Ali, F. Smarandache, Dynamic interval valued neutrosophic set: Modeling decision making in dynamic environments, *Computers in Industry*, 108 (2019) 45-52.
- [19] J. Ye, PID Tuning Method Using Single-Valued Neutrosophic Cosine Measure and Genetic Algorithm, *Intelligent Automation and Soft Computing*, 25 (2019) 15-23.
- [20] J. Ye, Multiple attribute group decision-making method with single-valued neutrosophic interval number information, *International Journal of Systems Science*, 50 (2019) 152-162.
- [21] M. Abdel-Basset, A. Gamal, L.H. Son, F. Smarandache, A Bipolar Neutrosophic Multi Criteria Decision Making Framework for Professional Selection, *Applied Sciences-Basel*, 10 (2020) 22.
- [22] A. Al-Quran, H. Hashim, L. Abdullah, A Hybrid Approach of Interval Neutrosophic Vague Sets and DEMATEL with New Linguistic Variable, *Symmetry-Basel*, 12 (2020) 15.
- [23] L.A. Zadeh, Fuzzy Sets, in: *Information and Control*, 1965, pp. 338-356.
- [24] K.T. Atanassov, Intuitionistic fuzzy sets, *Fuzzy Sets and Systems*, 20 (1986) 87-96.
- [25] P. Liu, J. Liu, S.-M. Chen, Some intuitionistic fuzzy Dombi Bonferroni mean operators and their application to multi-attribute group decision making, *Journal of the Operational Research Society*, 69 (2018) 1-24.
- [26] F. Smarandache, A unifying field in logics: Neutrosophic logic, *Multiple-Valued Logic*, 8 (1999).
- [27] H. Wang, F. Smarandache, Y. Zhang, R. Sunderraman, single-valued neutrosophic sets, *Multispace and Multistructure*, 4 (2010) 410-413.
- [28] P. Biswas, S. Pramanik, B.C. Giri, TOPSIS method for multi-attribute group decision-making under single-valued neutrosophic environment, *Neural Computing & Applications*, 27 (2016) 727-737.
- [29] W. Jiang, Y.H. Shou, A Novel Single-Valued Neutrosophic Set Similarity Measure and Its Application in Multicriteria Decision-Making, *Symmetry-Basel*, 9 (2017) 14.
- [30] J. Ye, Multicriteria decision-making method using the correlation coefficient under single-valued neutrosophic environment, *International Journal of General Systems*, 42 (2013) 386-394.
- [31] Y.-J. Lai, T.-Y. Liu, C.-L. Hwang, TOPSIS for MODM, *European journal of operational research*, 76 (1994) 486-500.
- [32] C.T. Chen, Extensions of the TOPSIS for group decision-making under fuzzy environment, *Fuzzy Sets and Systems*, 114 (2000) 1-9.
-

- 
- [33] T.C. Chu, Selecting plant location via a fuzzy TOPSIS approach, *International Journal of Advanced Manufacturing Technology*, 20 (2002) 859-864.
  - [34] M. Braglia, M. Frosolini, R. Montanari, Fuzzy TOPSIS approach for failure mode, effects and criticality analysis, *Quality and Reliability Engineering International*, 19 (2003) 425-443.
  - [35] M.F. Chen, G.H. Tzeng, Combining grey relation and TOPSIS concepts for selecting an expatriate host country, *Mathematical and Computer Modelling*, 40 (2004) 1473-1490.
  - [36] D.L. Olson, Comparison of weights in TOPSIS models, *Mathematical and Computer Modelling*, 40 (2004) 721-727.
  - [37] M.A. Abo-Sinna, A.H. Amer, Extensions of TOPSIS for multi-objective large-scale nonlinear programming problems, *Applied Mathematics and Computation*, 162 (2005) 243-256.
  - [38] R. Bausys, E.K. Zavadskas, A. Kaklauskas, APPLICATION OF NEUTROSOPHIC SET TO MULTICRITERIA DECISION MAKING BY COPRAS, *Economic Computation and Economic Cybernetics Studies and Research*, 49 (2015) 91-105.
  - [39] I. Deli, M. Ali, F. Smarandache, Ieee, Bipolar Neutrosophic Sets and Their Application Based on Multi-Criteria Decision Making Problems, in: *International conference on Advanced Mechatronic systems*, Ieee, Beijing, PEOPLES R CHINA, 2015, pp. 249-254.
  - [40] Gaurav, M. Kumar, K. Bhutani, S. Aggarwal, Hybrid model for medical diagnosis using Neutrosophic Cognitive Maps with Genetic Algorithms, in: *IEEE International Conference on Fuzzy Systems (FUZZ-IEEE)*, Ieee, Istanbul, TURKEY, 2015.
  - [41] J. Ye, Aggregation operators of neutrosophic linguistic numbers for multiple attribute group decision making, *Springerplus*, 5 (2016) 11.
  - [42] J. Ye, Exponential operations and aggregation operators of interval neutrosophic sets and their decision making methods, *Springerplus*, 5 (2016) 18.
  - [43] J. Ye, The generalized Dice measures for multiple attribute decision making under simplified neutrosophic environments, *Journal of Intelligent & Fuzzy Systems*, 31 (2016) 663-671.
  - [44] S. Ashraf, S. Naz, H. Rashmanlou, M.A. Malik, Regularity of graphs in single valued neutrosophic environment, *Journal of Intelligent & Fuzzy Systems*, 33 (2017) 529-542.
  - [45] P.D. Liu, G.L. Tang, W.L. Liu, Induced generalized interval neutrosophic Shapley hybrid operators and their

- application in multi-attribute decision making, *Scientia Iranica*, 24 (2017) 2164-2181.
- [46] P.D. Liu, F. Teng, Multiple attribute group decision making methods based on some normal neutrosophic number Heronian Mean operators, *Journal of Intelligent & Fuzzy Systems*, 32 (2017) 2375-2391.
- [47] Y.X. Ma, J.Q. Wang, J. Wang, X.H. Wu, An interval neutrosophic linguistic multi-criteria group decision-making method and its application in selecting medical treatment options, *Neural Computing & Applications*, 28 (2017) 2745-2765.
- [48] R.X. Nie, J.Q. Wang, H.Y. Zhang, Solving Solar-Wind Power Station Location Problem Using an Extended Weighted Aggregated Sum Product Assessment (WASPAS) Technique with Interval Neutrosophic Sets, *Symmetry-Basel*, 9 (2017) 20.
- [49] J.J. Peng, J.Q. Wang, X.H. Wu, An extension of the ELECTRE approach with multi-valued neutrosophic information, *Neural Computing & Applications*, 28 (2017) S1011-S1022.
- [50] J. Ye, An extended TOPSIS method for multiple attribute group decision making based on single valued neutrosophic linguistic numbers, *Journal of Intelligent & Fuzzy Systems*, 28 (2015) 247-255.
- [51] A. Elhassouny, F. Smarandache, Ieee, Neutrosophic-simplified-TOPSIS Multi-Criteria Decision-Making using combined Simplified-TOPSIS method and Neutrosophics, in: *IEEE International Conference on Fuzzy Systems (FUZZ-IEEE) held as part of IEEE World Congress on Computational Intelligence (IEEE WCCI)*, Ieee, Vancouver, CANADA, 2016, pp. 2468-2474.
- [52] S. Nadaban, S. Dzitac, Neutrosophic TOPSIS: A General View, in: *6th International Conference on Computers Communications and Control (ICCCC)*, Ieee, Oradea, ROMANIA, 2016, pp. 250-253.
- [53] M. Abdel-Basset, M. Mohamed, F. Smarandache, A Hybrid Neutrosophic Group ANP-TOPSIS Framework for Supplier Selection Problems, *Symmetry-Basel*, 10 (2018) 22.
- [54] J. Chen, S.Z. Zeng, C.H. Zhang, An OWA Distance-Based, Single-Valued Neutrosophic Linguistic TOPSIS Approach for Green Supplier Evaluation and Selection in Low-Carbon Supply Chains, *International Journal of Environmental Research and Public Health*, 15 (2018) 15.
- [55] G. Xu, S. Wang, T. Yang, W. Jiang, A Neutrosophic Approach Based on TOPSIS Method to Image Segmentation, *International Journal of Computers Communications & Control*, 13 (2018) 1047-1061.
- [56] M. Abdel-Basset, M. Saleh, A. Gamal, F. Smarandache, An approach of TOPSIS technique for developing supplier selection with group decision making under type-2 neutrosophic number, *Applied Soft Computing*,

- 77 (2019) 438-452.
- [57] N.A. Nabeeh, F. Smarandache, M. Abdel-Basset, H.A. El-Ghareeb, A. Aboelfetouh, An Integrated Neutrosophic-TOPSIS Approach and Its Application to Personnel Selection: A New Trend in Brain Processing Brain Analysis, *Ieee Access*, 7 (2019) 29734-29744.
- [58] Nancy, H. Garg, A novel divergence measure and its based TOPSIS method for multi criteria decision-making under single-valued neutrosophic environment, *Journal of Intelligent & Fuzzy Systems*, 36 (2019) 101-115.
- [59] S.T. Tehrim, M. Riaz, A novel extension of TOPSIS to MCGDM with bipolar neutrosophic soft topology, *Journal of Intelligent & Fuzzy Systems*, 37 (2019) 5531-5549.
- [60] M. Sinn, Sequential Group Lending: A Mechanism to Raise the Repayment Rate in Microfinance, *Economica*, 80 (2013) 326-344.
- [61] T. Allen, Optimal (partial) group liability in microfinance lending, *Journal of Development Economics*, 121 (2016) 201-216.
- [62] A. Haldar, J.E. Stiglitz, Group Lending, Joint Liability, and Social Capital: Insights From the Indian Microfinance Crisis, *Polit. Soc.*, 44 (2016) 459-497.
- [63] N.K. Kumar, Dynamic Incentives in Microfinance Group Lending: An Empirical Analysis of Progressive Lending Mechanism (vol 2, pg 1, 2012), *Sage Open*, 6 (2016) 1.
- [64] Y.Y. Xu, W.L. Cheng, L.Y. Zhang, Switching from Group Lending to Individual Lending: The Experience at China's Largest Microfinance Institution, *Emerging Markets Finance and Trade*, 56 (2020) 1989-2006.
- [65] S. Cornee, D. Masclet, Long-term relationships, group lending, and peer monitoring in microfinance: Experimental evidence, *J. Behav. Exp. Econ.*, 100 (2022) 25.
- [66] D. Pamucar, G. Cirovic, The selection of transport and handling resources in logistics centers using Multi-Attributive Border Approximation area Comparison (MABAC), *Expert Systems with Applications*, 42 (2015) 3016-3028.
- [67] J.J. Peng, J.Q. Wang, J. Wang, H.Y. Zhang, X.H. Chen, Simplified neutrosophic sets and their applications in multi-criteria group decision-making problems, *International Journal of Systems Science*, 47 (2016) 2342-2358.
- [68] H. Wang, F. Smarandache, Y.Q. Zhang, R. Sunderraman, Single valued neutrosophic sets, *Multispace Multistruct*, (2010) 410-413.



- 
- [69] P. Majumdar, S.K. Samanta, On similarity and entropy of neutrosophic sets, *Journal of Intelligent & Fuzzy Systems*, 26 (2014) 1245-1252.
- [70] Y. Wang, Using the method of maximizing deviation to make decision for multiindices, *Journal of Systems Engineering & Electronics*, 8 (1997) 21-26.
- [71] E. Bolturk, A. Karasan, Prioritization of Investment Alternatives for a Hospital by Using Neutrosophic CODAS Method, *Journal of Multiple-Valued Logic and Soft Computing*, 33 (2019) 381-396.
- [72] D. Stanujkic, D. Karabasevic, G. Popovic, D. Pamucar, Z. Stevic, E.K. Zavadskas, F. Smarandache, A Single-Valued Neutrosophic Extension of the EDAS Method, *Axioms*, 10 (2021) 13.
- [73] X. Liu, Y. Xu, Z. Gong, F. Herrera, Democratic consensus reaching process for multi-person multi-criteria large scale decision making considering participants' individual attributes and concerns, *Information Fusion*, 77 (2022) 220-232.
- [74] Y.J. Xu, X.W. Wen, W.C. Zhang, A two-stage consensus method for large-scale multi-attribute group decision making with an application to earthquake shelter selection, *Computers & Industrial Engineering*, 116 (2018) 113-129.
- [75] Y.J. Xu, W.J. Dai, J. Huang, M.Q. Li, E. Herrera-Viedma, Some models to manage additive consistency and derive priority weights from hesitant fuzzy preference relations, *Information Sciences*, 586 (2022) 450-467.
- [76] X. Liu, Y.J. Xu, F. Herrera, Consensus model for large-scale group decision making based on fuzzy preference relation with self-confidence: Detecting and managing overconfidence behaviors, *Information Fusion*, 52 (2019) 245-256.
- [77] X. Liu, Y. Xu, R. Montes, F. Herrera, Social network group decision making: Managing self-confidence-based consensus model with the dynamic importance degree of experts and trust-based feedback mechanism, *Information Sciences*, 505 (2019) 215-232.
- [78] S. Zhu, J. Huang, Y. Xu, A consensus model for group decision making with self - confident linguistic preference relations, *International Journal of Intelligent Systems*, 36 (2021) 6360-6386.
- [79] L. Li, L. Qiu, X. Liu, Y. Xu, E. Herrera-Viedma, An improved HK model-driven consensus reaching for group decision making under interval-valued fuzzy preference relations with self-confidence, *Computers & Industrial Engineering*, 171 (2022) 108438.
- [80] A.P. Darko, D.C. Liang, Probabilistic linguistic WASPAS method for patients' prioritization by developing

- prioritized Maclaurin symmetric mean aggregation operators, *Applied Intelligence*, 52 (2022) 9537-9555.
- [81] Q. Pang, H. Wang, Z.S. Xu, Probabilistic linguistic linguistic term sets in multi-attribute group decision making, *Information Sciences*, 369 (2016) 128-143.
- [82] M.W. Lin, Z.S. Xu, Y.L. Zhai, Z.Q. Yao, Multi-attribute group decision-making under probabilistic uncertain linguistic environment, *Journal of the Operational Research Society*, 69 (2018) 157-170.
- [83] Y.Y. Yuan, Z.S. Xu, Y.X. Zhang, The DEMATEL-COPRAS hybrid method under probabilistic linguistic environment and its application in Third Party Logistics provider selection, *Fuzzy Optimization and Decision Making*, 21 (2022) 137-156.

Received: Month Day, Year. Accepted: Month Day, Year

---

---

# MABAC Method for Multiple Attribute Group Decision Making under Single-Valued Neutrosophic Sets and Applications to Performance Evaluation of Sustainable Microfinance Groups Lending

Hui Ran

College of Finance and Logistics Management, LiuZhou Vocational & Technical College, Liuzhou, 545006, Guangxi, China

\*Corresponding author, E-mail: ranhui0808@163.com

**Abstract:** As an important supplement to my country's financial institutions, micro-loan companies serve "agriculture, rural areas and farmers", small and micro enterprises, and individuals, to a certain extent, alleviating the financing difficulties of such groups and regulating private finance. However, micro-loan companies only lend but do not deposit. In the process of lending, due to inadequate risk management, the risk problem has become increasingly prominent. With the continuous growth of the loan amount of rural credit and the continuous increase of microfinance groups lending customers, it faces certain problems in its risk management, which increases the risks of the company in all aspects. The performance evaluation of sustainable microfinance groups lending is a classical MAGDM issues. In such paper, the Hamming distances of single-valued neutrosophic sets (SVNSs) and maximizing deviation method (MDM) is used to obtain the attribute weights and the single-valued neutrosophic numbers MABAC(SVNN-MABAC) method is structured for MAGDM under SVNSs. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVNN-MABAC.

**Keywords:** MAGDM; single-valued neutrosophic sets (SVNSs); MABAC method; MDM; performance evaluation; microfinance groups lending

---

## 1. Introduction

The MADM is a kind of very complex optimization decision-making problem, which often occurs in the field of decision engineering, economics, military, and public management[1-5]. In the process of MADM, the value of decision-making attributes often has information uncertainty, and the data is difficult to estimate, predict, and evaluate[6-13]. This is more general than the decision attribute value is accurate data and clear

information. Decision problems have multiple decision attributes[14-17]. For qualitative decision attributes, the decision attribute values are usually presented in the form of language evaluation, such as excellent, good, qualified, unqualified and other semantic information, which brings difficulties to mathematical calculation and analysis, simply quantitative conversion of semantic information, such as setting grades, cannot guarantee scientificity, and it is easy to lose important information, resulting in decision-making mistakes[18-22]. Zadeh [23] structured the fuzzy sets (FSs). Then, Atanassov [24] structured defined intuitionistic fuzzy sets (IFSs). Liu et al. [25] defined the Dombi BM operations for MAGDM. Smarandache [26] structured the neutrosophic sets (NSs). However, considering that the medium intelligence set is defined in a non-standard sub interval, which is not convenient for application in engineering and natural science, Wang et al. [27] proposed the SVNNS to solve this problem. It is a subclass of the medium intelligence set. It uses true membership, false membership and uncertainty functions to describe decision information together, which can be easily applied in engineering, science and other fields. SVNNSs have many obvious advantages in dealing with uncertain and fuzzy decision information, and a lot of research has been done on this. Biswas, Pramanik and Giri [28] used SVNNSs to represent decision information and TOPSIS to propose MADM method. Jiang and Shou [29] proposed the similarity measurement for SVNNSs based on Dempster Shafer distance theory. Ye [30] proposed a decision weighted correlation coefficient of SVNNSs, and proposed a MADM with cross entropy of SVNNSs. The key roles of TOPSIS [31] is that the distance between the optimal scheme and the positive ideal scheme should be the shortest, and the distance between the optimal scheme and the negative ideal scheme should be the farthest. The combination of TOPSIS method [32-37] and SVNNSs [38-49] can effectively solve the MADM problem [50-59].

Pamucar and Cirovic [60] first proposed the MABAC method in 2015. The basic idea of MABAC method is to calculate the value of the alternative criterion function and define the distance between the criterion function and the boundary approximation region[61-68]. Therefore, all alternatives can be combined into the boundary, upper approximate area or the lower approximation area. Then, rank the alternatives. In such paper, the Hamming distances of SVNNSs and MDM is used to obtain the attribute decision weights and the single-valued neutrosophic MABAC(SVNN-MABAC) method is structured for MAGDM under single-valued neutrosophic sets (SVNNSs). Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVNN-MABAC. The main

advantages of the SVN-MABAC method are given as follows: the computing results by SVN-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains and losses into account; it is available to combine this model with other approaches. Hence, the SVN-MABAC method is a good tool to derive reasonable decision-making results.

The reminder of our paper proceeds. The SVN is reviewed in Sec. 2. The SVN-MABAC method for MAGDM is defined in Sec. 3. An example for performance evaluation of sustainable microfinance groups lending is given to show the superiority in Sec. 4. the conclusion is fully given in Sec. 5.

## 2. Preliminaries

Wang et al. [27] defined the given SVN

**Definition 1** [27]. The SVN  $A$  in  $Y$  is defined:

$$YA = \{(y, AT(y), AI(y), AF(y)) | y \in Y\} \quad (1)$$

with defined truth-membership  $AT(y)$ , defined indeterminacy-membership  $AI(y)$  and defined falsity-membership  $AF(y)$ ,  $AT(y), AI(y), AF(y) \in [0, 1]$ ,  $0 \leq AT(y) + AI(y) + AF(y) \leq 3$ .

The SVN is expressed as  $YA = (AT, AI, AF)$ ,  $AT, AI, AF \in [0, 1]$ ,  $0 \leq AT + AI + AF \leq 3$ .

**Definition 2** [69]. Let  $YA = (AT, AI, AF)$  be the SVN, the score value is:

$$SV(YA) = \frac{(2 + AT - AI - AF)}{3}, \quad SV(YA) \in [0, 1]. \quad (2)$$

**Definition 3** [69]. Let  $YA = (AT, AI, AF)$  be the SVN, the accuracy value is:

$$HV(YA) = AT - AF, \quad HV(YA) \in [-1, 1]. \quad (3)$$

Peng et al. [69] came up with order decision relation for SVN.

**Definition 4** [69]. Let  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$  be two given SVN, let

$$SV(YA) = \frac{(2 + AT - AI - AF)}{3} \quad \text{and} \quad SV(YB) = \frac{(2 + BT - BI - BF)}{3}, \quad \text{and} \quad \text{let}$$

$HV(YA) = AT - AF$  and  $HV(YB) = BT - BF$ , if  $SV(YA) < SV(YB)$ ,  $YA < YB$ ; if

$SV(YA) = SV(YB)$ , then (1) if  $HV(YA) = HV(YB)$ ,  $YA = YB$ ; (2) if  $HV(YA) < HV(YB)$ ,

$YA < YB$ .

**Definition 5**[70]. Let  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$  be two SVNNS, the basic operations are defined:

- (1)  $YA \oplus YB = (AT + BT - AT \cdot BT, AI \cdot BI, AF \cdot BF)$ ;
- (2)  $YA \otimes YB = (AT \cdot BT, AI + BI - AI \cdot BI, AF + BF - AF \cdot BF)$ ;
- (3)  $\lambda YA = (1 - (1 - AT)^\lambda, (AI)^\lambda, (AF)^\lambda), \lambda > 0$ ;
- (4)  $(YA)^\lambda = ((AT)^\lambda, (AI)^\lambda, 1 - (1 - AF)^\lambda), \lambda > 0$ .

**Definition 6**[71]. Let  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$ , then the Hamming distance between  $YA = (AT, AI, AF)$  and  $YB = (BT, BI, BF)$  is defined:

$$HD(YA, YB) = \frac{|AT - BT| + |AI - BI| + |AF - BF|}{3} \quad (4)$$

### 3. The MABAC method for MAGDM with SVNNS

Let  $ZZ = \{ZZ_1, ZZ_2, \dots, ZZ_n\}$  be the set of attributes,  $WZ = \{WZ_1, WZ_2, \dots, WZ_n\}$  be the weight of attributes  $ZZ_j$ . Let  $PP = \{PP_1, PP_2, \dots, PP_m\}$  be alternatives. And  $AQ = (aq_{ij})_{m \times n} = (AT_{ij}, AI_{ij}, AF_{ij})_{m \times n}$  is the SVNN matrix. Integrating the MABAC method for MAGDM with SVNNS, we build the SVNN-MABAC method with SVNNS. The SVNN-MABAC procedures can be described subsequently.

**Step 1.** Set up the SVNN matrix  $AQ = (aq_{ij})_{m \times n} = (AT_{ij}, AI_{ij}, AF_{ij})_{m \times n}$ .

$$AQ = (aq_{ij})_{m \times n} = \begin{bmatrix} aq_{11} & aq_{12} & \dots & aq_{1n} \\ aq_{21} & aq_{22} & \dots & aq_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ aq_{m1} & aq_{m2} & \dots & aq_{mn} \end{bmatrix} \quad (6)$$

**Step 2.** Normalize matrix  $AQ = (aq_{ij})_{m \times n}$  to  $NQ = [nq_{ij}]_{m \times n}$ .

$$\begin{aligned} nq_{ij} &= (NT_{ij}, NI_{ij}, NF_{ij}) \\ &= \begin{cases} (AT_{ij}, AI_{ij}, AF_{ij}), & ZZ_j \text{ is a benefit criterion} \\ (AF_{ij}, AI_{ij}, AT_{ij}), & ZZ_j \text{ is a cost criterion} \end{cases} \end{aligned} \quad (8)$$

**Step 3.** Utilize the MDM to determine the weight of attributes.

The MDM [72] is used to derive the weight values.

- (1) Depending on the  $NQ = [nq_{ij}]_{m \times n}$ , the deviation of  $PP_i$  from other alternatives is calculated.

$$SVNNHD_{ij} = \sum_{t=1}^m w_{z_j} \cdot HD(nq_{ij}, nq_{tj}) \quad (9)$$

$$\text{where } HD(nq_{ij}, nq_{tj}) = \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3}.$$

(2) Calculate the weighted deviation.

$$\begin{aligned} SVNNHD_j(wz) &= \sum_{i=1}^m SVNNHD_{ij}(wz) \\ &= \sum_{i=1}^m \sum_{t=1}^m w_{z_j} \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right) \end{aligned} \quad (10)$$

(3) Construct the programming model.

$$(M-1) \begin{cases} \max D(wz) = \sum_{j=1}^n \sum_{i=1}^m \sum_{t=1}^m w_{z_j} \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right) \\ \text{s.t. } wz_j \geq 0, \sum_{j=1}^n wz_j^2 = 1 \end{cases} \quad (11)$$

To solve this defined model, The Lagrange function is used to solve this model.

$$L(wz, \xi) = \sum_{j=1}^n \sum_{i=1}^m \sum_{t=1}^m w_{z_j} \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right) + \frac{\xi}{2} \left( \sum_{j=1}^n wz_j^2 - 1 \right)$$

where  $\xi$  is the Lagrange decision multiplier, the partial derivatives are obtained.

$$\begin{cases} \frac{\partial L}{\partial wz_j} = \sum_{i=1}^m \sum_{t=1}^m \left( \frac{|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{3} \right) + \xi wz_j = 0 \\ \frac{\partial L}{\partial \xi} = \frac{1}{2} \left( \sum_{j=1}^n wz_j^2 - 1 \right) = 0 \end{cases}$$

And the weight information is obtained.

$$wz_j^* = \frac{\sum_{i=1}^m \sum_{t=1}^m |NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|}{\sqrt{\sum_{j=1}^n \left( \sum_{i=1}^m \sum_{t=1}^m (|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|) \right)^2}}$$

Finally, the normalized weights are obtained.

$$wz_j = \frac{\sum_{i=1}^m \sum_{t=1}^m (|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|)}{\sum_{j=1}^n \sum_{i=1}^m \sum_{t=1}^m (|NT_{ij} - NT_{tj}| + |NI_{ij} - NI_{tj}| + |NF_{ij} - NF_{tj}|)} \quad (12)$$

**Step 4.** Obtain the weighted matrix  $OQ = (oq_{ij})_{m \times n}$ :

$$\begin{aligned}
 oq_{ij} &= (WNT_{ij}, WNI_{ij}, WNF_{ij}) \\
 &= wz_j \cdot nq_{ij} = \left(1 - (1 - NT_{ij})^{wz_j}, (NI_{ij})^{wz_j}, (NF_{ij})^{wz_j}\right)
 \end{aligned} \tag{13}$$

**Step 5.** Obtain the defined SVN border approximation area (SVNNBAA)  $GQ = (gq_j)_{1 \times n}$ .

$$gq_j = \prod_{i=1}^m (oq_{ij})^{1/m} = \left( \prod_{i=1}^m (WNT_{ij})^{1/m}, \prod_{i=1}^m (WNI_{ij})^{1/m}, 1 - \prod_{i=1}^m (1 - WNF_{ij})^{1/m} \right) \tag{14}$$

**Step 6.** Obtain the SVN distance decision matrix  $DQ = (dq_{ij})_{m \times n}$  from SVNNBAA with Eq. (15).

$$dq_{ij} = \begin{cases} (HD(oq_{ij}, gq_j)), & \text{if } SV(oq_{ij}) \geq S(gq_j), \\ -HD(oq_{ij}, gq_j), & \text{if } SV(oq_{ij}) < S(gq_j), \end{cases} \tag{15}$$

**Step 7.** Obtain the final order value  $SVNNF_i$ .

$$SVNNF_i = \sum_{j=1}^n dq_{ij} \tag{16}$$

**Step 8.** The given alternatives can be order with  $SVNNF_i$ . The higher information value of  $SVNNF_i$  is, the optimal selection will be.

## 4. The Empirical Example and Comparative analysis

### 4.1 An empirical example

Microfinance is an institutionalized form of credit that provides credit services to the low-income poor. Starting from the mid-1970s, some developing countries in Asia and Latin America, recognizing the disadvantaged position of the poor in the formal financial market, borrowed some features of traditional private credit and modern management experience, combined with the economic and social conditions of the countries where they are located and the economic and cultural characteristics of the poor, and on the basis of continuous exploration and experimentation, creatively constructed a variety of Credit systems and methods. Since most of the institutional arrangements of such credit modalities are aimed at the self-employed poor with normal production capacity, and they are designed to treat the self-employed poor households and the economic activities they are engaged in as micro-enterprises. Under these assumptions, this type of credit service for the poor is referred to as microenterprise credit or microcredit for short. When this approach was introduced in our country, it was translated as microcredit. The situation between Internet financial enterprises and traditional commercial banks is not a "zero-sum game". Compared with traditional financial service products, Internet



financial wealth management products are more substitutable. In this context, subject to the gradually approaching market pressure of Internet finance, traditional commercial banks must actively carry out reforms and innovations if they want to calmly deal with and reverse the adversity. Therefore, commercial banks must change the traditional commercial banking business operation model of "sugar daddy, large households, relying on resources, and profit margins", and actively take measures to deal with the crises and challenges brought by Internet financial products. In recent years, the development momentum of my country's Internet finance has been particularly rapid. However, with the continuous decision improvement of the socialist market economic with Chinese characteristics, the industry environment for the development of my country's Internet finance has been gradually standardized, but at the same time, new problems have emerged. From the perspective of the development of microfinance business, Internet finance has spawned a wide variety of business products. However, due to the influence of factors such as lack of industry supervision, commercial banks' microfinance business risk events frequently occur, which is not conducive to commercial banks' sustainable operations. The performance evaluation of sustainable microfinance groups lending is the MAGDM. In this paper, an empirical application of performance evaluation of sustainable microfinance groups lending will be provided with SVNN-MABAC. There are five microfinance groups  $PP_i (i = 1, 2, 3, 4, 5)$  are to evaluated the performance of sustainable microfinance groups lending. In order to assess these microfinance groups fairly, the experts group give their assessment with four defined attributes: ① $ZZ_1$  is the pay back ability; ② $ZZ_2$  is the loan amount; ③ $ZZ_3$  is the loan utilization rate; ④ $ZZ_4$  is the loan repayment ability. Evidently,  $ZZ_2$  is the cost, others are the benefit. Then, the SVNN-MABAC method is applied to MAGDM for solving the performance evaluation of sustainable microfinance groups lending with SVNNs. The built SVNN-MABAC method involves the following steps:

**Step 1.** Set up the SVNN-matrix  $AQ = (aq_{ij})_{5 \times 4}$  as in Table 1.

**Table 1.** SVNN information

|        | $ZZ_1$             | $ZZ_2$             | $ZZ_3$             | $ZZ_4$             |
|--------|--------------------|--------------------|--------------------|--------------------|
| $PP_1$ | (0.53, 0.35, 0.37) | (0.26, 0.25, 0.22) | (0.50, 0.35, 0.50) | (0.33, 0.33, 0.35) |
| $PP_2$ | (0.55, 0.25, 0.55) | (0.58, 0.53, 0.23) | (0.52, 0.07, 0.59) | (0.55, 0.23, 0.55) |
| $PP_3$ | (0.35, 0.07, 0.55) | (0.53, 0.32, 0.38) | (0.53, 0.07, 0.58) | (0.53, 0.29, 0.58) |
| $PP_4$ | (0.33, 0.33, 0.33) | (0.52, 0.02, 0.22) | (0.55, 0.53, 0.55) | (0.33, 0.33, 0.36) |

|                 |                    |                    |                    |                    |
|-----------------|--------------------|--------------------|--------------------|--------------------|
| PP <sub>5</sub> | (0.35, 0.09, 0.35) | (0.32, 0.05, 0.29) | (0.59, 0.35, 0.53) | (0.33, 0.33, 0.33) |
|-----------------|--------------------|--------------------|--------------------|--------------------|

**Step 2.** Normalize  $AQ = (aq_{ij})_{5 \times 4}$  to  $NQ = [nq_{ij}]_{5 \times 4}$  (See Table 2).

**Table 2.** The normalized SVN information

|                 | $ZZ_1$             | $ZZ_2$             | $ZZ_3$             | $ZZ_4$             |
|-----------------|--------------------|--------------------|--------------------|--------------------|
| PP <sub>1</sub> | (0.53, 0.35, 0.37) | (0.22, 0.25, 0.26) | (0.50, 0.35, 0.50) | (0.33, 0.33, 0.35) |
| PP <sub>2</sub> | (0.55, 0.25, 0.55) | (0.23, 0.53, 0.58) | (0.52, 0.07, 0.59) | (0.55, 0.23, 0.55) |
| PP <sub>3</sub> | (0.35, 0.07, 0.55) | (0.38, 0.32, 0.53) | (0.53, 0.07, 0.58) | (0.53, 0.29, 0.58) |
| PP <sub>4</sub> | (0.33, 0.33, 0.33) | (0.22, 0.02, 0.52) | (0.55, 0.53, 0.55) | (0.33, 0.33, 0.36) |
| PP <sub>5</sub> | (0.35, 0.09, 0.35) | (0.29, 0.05, 0.32) | (0.59, 0.35, 0.53) | (0.33, 0.33, 0.33) |

**Step 3.** Obtain the attribute weights in Table 3.

**Table 3.** The attributes weights

|        | $ZZ_1$ | $ZZ_2$ | $ZZ_3$ | $ZZ_4$ |
|--------|--------|--------|--------|--------|
| $wz_j$ | 0.2574 | 0.1898 | 0.2667 | 0.2861 |

**Step 4.** Obtain the weighted matrix  $OQ = (oq_{ij})_{m \times n}$  (Table 4).

**Table 4.** SVN weighted normalized values

| $ZZ_1$                   | $ZZ_2$                   |
|--------------------------|--------------------------|
| (0.2266, 0.2078, 0.2624) | (0.2066, 0.2427, 0.2642) |
| (0.2262, 0.2406, 0.4626) | (0.4404, 0.2246, 0.2468) |
| (0.2242, 0.4224, 0.4644) | (0.4026, 0.2422, 0.4682) |
| (0.4602, 0.2268, 0.2066) | (0.2400, 0.2422, 0.6200) |
| (0.2422, 0.4268, 0.2462) | (0.2264, 0.4206, 0.2606) |
| $ZZ_3$                   | $ZZ_4$                   |
| (0.4622, 0.4266, 0.4084) | (0.4664, 0.2487, 0.2222) |

|                          |                           |
|--------------------------|---------------------------|
| (0.2244, 0.4264, 0.4442) | (0.2424, 0.2267, 0.4468)  |
| (0.2622, 0.002, 0.2422)  | (0.2624, 0.2442, 0.2426)  |
| (0.2226, 0.2008, 0.2622) | (0.2224, 0.28607, 0.2266) |
| (0.2242, 0.4244, 0.4666) | (0.2020, 0.2067, 0.4660)  |

**Step 5.** Determine the SVNNBAA (Table 5).

**Table 5. SVNNBAA**

| SVNNBAA |                          |
|---------|--------------------------|
| $ZZ_1$  | (0.3322, 0.2362, 0.2223) |
| $ZZ_2$  | (0.3633, 0.003, 0.3233)  |
| $ZZ_3$  | (0.3336, 0.3006, 0.3633) |
| $ZZ_4$  | (0.2633, 0.2366, 0.2062) |

**Step 6.** Calculate the  $DQ = (dq_{ij})_{5 \times 4}$  (Table 5).

**Table 5. Distance matrix**

|        | $ZZ_1$  | $ZZ_2$  | $ZZ_3$  | $ZZ_4$  |
|--------|---------|---------|---------|---------|
| $PP_1$ | -0.0837 | 0.0255  | 0.0400  | -0.1022 |
| $PP_2$ | 0.1320  | -0.0690 | 0.1297  | -0.1421 |
| $PP_3$ | -0.1054 | -0.0461 | -0.1078 | -0.1162 |
| $PP_4$ | -0.0480 | -0.0387 | -0.0293 | -0.1063 |
| $PP_5$ | -0.1227 | -0.0648 | -0.1418 | -0.2150 |

**Step 7.** Calculate  $SVNNF_i$  in Table 6.

**Table 6. The SVNNF values**

| Alternative | SVNNF value |
|-------------|-------------|
| $PP_1$      | -0.1204     |

|        |         |
|--------|---------|
| $PP_2$ | 0.0506  |
| $PP_3$ | -0.3755 |
| $PP_4$ | -0.2223 |
| $PP_5$ | -0.5443 |

**Step 8.** From the Table 6, the order is:  $PP_2 > PP_1 > PP_4 > PP_3 > PP_5$  and  $PP_2$  is the optimal selection.

#### 4.2 Compare analysis

The SVN-MABAC is made comparison with SVNWA & SVNWG operators[69], SVN-CODAS method[73] and SVN-EDAS method[74]. The decision results of different methods are in Table7.

**Table 7. Results for different given methods**

| Methods          | Order                              | The optimal choice | The worst choice |
|------------------|------------------------------------|--------------------|------------------|
| SVNWA [69]       | $PP_2 > PP_4 > PP_5 > PP_1 > PP_3$ | $PP_2$             | $PP_3$           |
| SVNWG [69]       | $PP_2 > PP_4 > PP_1 > PP_5 > PP_3$ | $PP_2$             | $PP_3$           |
| SVN-CODAS [73]   | $PP_2 > PP_1 > PP_4 > PP_5 > PP_3$ | $PP_2$             | $PP_3$           |
| SVN-EDAS [74]    | $PP_2 > PP_5 > PP_4 > PP_1 > PP_3$ | $PP_2$             | $PP_3$           |
| SVN-MABAC method | $PP_2 > PP_1 > PP_4 > PP_3 > PP_5$ | $PP_2$             | $PP_3$           |

From Table 7, obviously, the best enterprise given is  $PP_2$  in the five given methods, and the worst selection is  $PP_3$  in most cases. In other words, the order of these five methods have light difference. Different decision methods may effectively solve the MAGDM problem from different research decision angles. These five given models have their given advantages: (1) the SVNWA operator emphasis group decision influences;

(2) the SVNNWG operator emphasis individual decision influences; (3) In the SVNN-CODAS method, the overall performance of the alternatives is measured by Euclidean distance and Hamming distance of negative ideal points, where Euclidean distance is used as the main measure for evaluation. If the Euclidean distance between two alternatives is very close, then the Hamming distance is used to compare the two alternatives. Among them, the closeness of the Euclidean distance can be determined by using the threshold parameter; (4) The SVNN-EDAS method has required fewer computations, although it results in the same ranking of alternatives. The evaluations of alternatives in EDAS method based on distance measures from the average solutions in terms of each criterion unlike TOPSIS and VIKOR. (5) The SVNN-MABAC method has a large amount of precious characteristic, such as: the computing results by SVNN-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains and losses into account; it is available to combine this model with other approaches. Hence, the SVNN-MABAC method is a good tool to derive reasonable decision making results.

## 5. Conclusion

In recent years, the development of Internet finance has shown an unprecedented prosperous trend, which is the result of the rapid decision development of Internet information technology and cloud technology. Under this background, there are endless cases of innovation and entrepreneurship in the domestic Internet finance field, especially the development of Internet wealth management products. Especially quickly. In 2014, Alibaba Finance launched the "Yue Bao" service for the first time, mainly providing Alipay wealth management services. This product is a wealth management fund product jointly launched by Alipay and Tianhong Fund. Money market financial instruments with high security and stability, such as certificates of deposit. Once the Yu'e Bao product was launched, it aroused strong reactions in the financial investment market. It is known as a "wealth management artifact" due to its low threshold and fast receipt of income. Under this wave, other Internet financial companies have followed closely and launched various wealth management products, such as Baidu's "Baifa", Suning's "Change Money", Tencent's "Wealth Management", etc. Financial markets are showing unprecedented prosperity. The performance evaluation of sustainable microfinance groups lending is the MAGDM. In this given paper, the MABAC method is built for SVNN-MAGDM. First, the Hamming distances of SVNSs and MDM is employed to obtained the decision weights and the SVNN-MABAC method is structured for MAGDM under SVNSs. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVNN-MABAC. The main contributions of this work are (1) The attribute weights are obtained by MDM method; (2) the paper constructs the SVNN-MABAC method for performance evaluation of sustainable microfinance groups lending; (3) the established method is illustrated by a case study for performance evaluation of sustainable microfinance groups lending; and (4) some comparisons prove the rationality and advantages. Therefore, we have more and more reasons to believe that the improved SVNN-MABAC decision model will be more widely used in different MAGDM issues, such as supplier selection, factory location, online reviews and so on[75-88].

## References

- [1] X.D. Peng, F. Smarandache, New multiparametric similarity measure for neutrosophic set with big data industry evaluation, *Artificial Intelligence Review*, 53 (2020) 3089-3125.
- [2] N.X. Thao, F. Smarandache, Apply new entropy based similarity measures of single valued neutrosophic sets to select supplier material, *Journal of Intelligent & Fuzzy Systems*, 39 (2020) 1005-1019.
- [3] R. Chutia, F. Smarandache, Ranking of single-valued neutrosophic numbers through the index of optimism and its reasonable properties, *Artificial Intelligence Review*, 55 (2022) 1489-1518.
- [4] Z. Turskis, R. Bausys, F. Smarandache, G. Kazakeviciute-Januskeviciene, E.K. Zavadskas, M-generalised q-neutrosophic extension of CoCoSo method, *International Journal of Computers Communications & Control*, 17 (2022) 12.
- [5] S.Z. Zeng, S. Ali, M.K. Mahmood, F. Smarandache, D. Ahmad, Decision-Making Problems under the Environment of m-Polar Diophantine Neutrosophic N-Soft Set, *Cmes-Computer Modeling in Engineering & Sciences*, 130 (2022) 581-606.
- [6] S.A. Edalatpanah, Neutrosophic structured element, *Expert Systems*, 37 (2020) 17.
- [7] H. Eroglu, R. Sahin, A Neutrosophic VIKOR Method-Based Decision-Making with an Improved Distance Measure and Score Function: Case Study of Selection for Renewable Energy Alternatives, *Cognitive Computation*, 12 (2020) 1338-1355.
- [8] Y.M. Gong, Z.Y. Ma, M.J. Wang, X.Y. Deng, W. Jiang, A New Multi-Sensor Fusion Target Recognition Method Based on Complementarity Analysis and Neutrosophic Set, *Symmetry-Basel*, 12 (2020) 18.
- [9] M.R. Hashmi, M. Riaz, F. Smarandache, m-polar Neutrosophic Generalized Weighted and m-polar Neutrosophic Generalized Einstein Weighted Aggregation Operators to Diagnose Coronavirus (COVID-19), *Journal of Intelligent & Fuzzy Systems*, 39 (2020) 7381-7401.
- [10] A.M. Khalil, D.Q. Cao, A. Azzam, F. Smarandache, W.R. Alharbi, Combination of the Single-Valued Neutrosophic Fuzzy Set and the Soft Set with Applications in Decision-Making, *Symmetry-Basel*, 12 (2020) 17.
- [11] B. Ning, G. Wei, R. Lin, Y. Guo, A novel MADM technique based on extended power generalized Maclaurin symmetric mean operators under probabilistic dual hesitant fuzzy setting and its application to sustainable suppliers selection, *Expert Systems with Applications*, 204 (2022) 117419.
- [12] S. Wang, G. Wei, J. Lu, J. Wu, C. Wei, X. Chen, GRP and CRITIC method for probabilistic uncertain linguistic MAGDM and its application to site selection of hospital constructions, *Soft Computing*, 26 (2022) 237-251.
- [13] M. Zhao, H. Gao, G. Wei, C. Wei, Y. Guo, Model for network security service provider selection with probabilistic uncertain linguistic TODIM method based on prospect theory, *Technological and Economic Development of Economy*, 28 (2022) 638-654.
- [14] H.P. Ren, H.H. Chen, W. Fei, D.F. Li, A MAGDM Method Considering the Amount and Reliability Information of Interval-Valued Intuitionistic Fuzzy Sets, *International Journal of Fuzzy Systems*, 19 (2017) 715-725.
- [15] M.R. Feylizadeh, A. Mahmoudi, M. Bagherpour, D.F. Li, Project crashing using a fuzzy multi-objective model considering time, cost, quality and risk under fast tracking technique: A case study, *Journal of Intelligent & Fuzzy Systems*, 35 (2018) 3615-3633.
- [16] D.F. Li, Y.T. Wang, A. Madden, Y. Ding, J. Tang, G.G. Sun, N. Zhang, E.G. Zhou, Analyzing stock market trends using social media user moods and social influence, *Journal of the Association for Information Science and Technology*, 70 (2019) 1000-1013.
- [17] X.Y. Xiong, P. Zhou, Y.Q. Yin, T.C.E. Cheng, D.F. Li, An exact branch-and-price algorithm for multitasking

scheduling on unrelated parallel machines, *Naval Research Logistics*, 66 (2019) 502-516.

[18] N.T. Thong, L.Q. Dat, L.H. Son, N.D. Hoa, M. Ali, F. Smarandache, Dynamic interval valued neutrosophic set: Modeling decision making in dynamic environments, *Computers in Industry*, 108 (2019) 45-52.

[19] J. Ye, PID Tuning Method Using Single-Valued Neutrosophic Cosine Measure and Genetic Algorithm, *Intelligent Automation and Soft Computing*, 25 (2019) 15-23.

[20] J. Ye, Multiple attribute group decision-making method with single-valued neutrosophic interval number information, *International Journal of Systems Science*, 50 (2019) 152-162.

[21] M. Abdel-Basset, A. Gamal, L.H. Son, F. Smarandache, A Bipolar Neutrosophic Multi Criteria Decision Making Framework for Professional Selection, *Applied Sciences-Basel*, 10 (2020) 22.

[22] A. Al-Quran, H. Hashim, L. Abdullah, A Hybrid Approach of Interval Neutrosophic Vague Sets and DEMATEL with New Linguistic Variable, *Symmetry-Basel*, 12 (2020) 15.

[23] L.A. Zadeh, Fuzzy Sets, in: *Information and Control*, 1965, pp. 338-356.

[24] K.T. Atanassov, Intuitionistic fuzzy sets, *Fuzzy Sets and Systems*, 20 (1986) 87-96.

[25] P. Liu, J. Liu, S.-M. Chen, Some intuitionistic fuzzy Dombi Bonferroni mean operators and their application to multi-attribute group decision making, *Journal of the Operational Research Society*, 69 (2018) 1-24.

[26] F. Smarandache, A unifying field in logics: Neutrosophic logic, *Multiple-Valued Logic*, 8 (1999).

[27] H. Wang, F. Smarandache, Y. Zhang, R. Sunderraman, single-valued neutrosophic sets, *Multispace and Multistructure*, 4 (2010) 410-413.

[28] P. Biswas, S. Pramanik, B.C. Giri, TOPSIS method for multi-attribute group decision-making under single-valued neutrosophic environment, *Neural Computing & Applications*, 27 (2016) 727-737.

[29] W. Jiang, Y.H. Shou, A Novel Single-Valued Neutrosophic Set Similarity Measure and Its Application in Multicriteria Decision-Making, *Symmetry-Basel*, 9 (2017) 14.

[30] J. Ye, Multicriteria decision-making method using the correlation coefficient under single-valued neutrosophic environment, *International Journal of General Systems*, 42 (2013) 386-394.

[31] Y.-J. Lai, T.-Y. Liu, C.-L. Hwang, TOPSIS for MODM, *European journal of operational research*, 76 (1994) 486-500.

[32] C.T. Chen, Extensions of the TOPSIS for group decision-making under fuzzy environment, *Fuzzy Sets and Systems*, 114 (2000) 1-9.

[33] T.C. Chu, Selecting plant location via a fuzzy TOPSIS approach, *International Journal of Advanced Manufacturing Technology*, 20 (2002) 859-864.

[34] M. Braglia, M. Frosolini, R. Montanari, Fuzzy TOPSIS approach for failure mode, effects and criticality analysis, *Quality and Reliability Engineering International*, 19 (2003) 425-443.

[35] M.F. Chen, G.H. Tzeng, Combining grey relation and TOPSIS concepts for selecting an expatriate host country, *Mathematical and Computer Modelling*, 40 (2004) 1473-1490.

[36] D.L. Olson, Comparison of weights in TOPSIS models, *Mathematical and Computer Modelling*, 40 (2004) 721-727.

[37] M.A. Abo-Sinna, A.H. Amer, Extensions of TOPSIS for multi-objective large-scale nonlinear programming problems, *Applied Mathematics and Computation*, 162 (2005) 243-256.

[38] R. Bausys, E.K. Zavadskas, A. Kaklauskas, APPLICATION OF NEUTROSOPHIC SET TO MULTICRITERIA DECISION MAKING BY COPRAS, *Economic Computation and Economic Cybernetics Studies and Research*, 49 (2015) 91-105.

[39] I. Deli, M. Ali, F. Smarandache, Ieee, Bipolar Neutrosophic Sets and Their Application Based on Multi-Criteria Decision Making Problems, in: *International conference on Advanced Mechatronic systems*, Ieee,

Beijing, PEOPLES R CHINA, 2015, pp. 249-254.

[40] Gaurav, M. Kumar, K. Bhutani, S. Aggarwal, Hybrid model for medical diagnosis using Neutrosophic Cognitive Maps with Genetic Algorithms, in: IEEE International Conference on Fuzzy Systems (FUZZ-IEEE), Ieee, Istanbul, TURKEY, 2015.

[41] J. Ye, Aggregation operators of neutrosophic linguistic numbers for multiple attribute group decision making, Springerplus, 5 (2016) 11.

[42] J. Ye, Exponential operations and aggregation operators of interval neutrosophic sets and their decision making methods, Springerplus, 5 (2016) 18.

[43] J. Ye, The generalized Dice measures for multiple attribute decision making under simplified neutrosophic environments, Journal of Intelligent & Fuzzy Systems, 31 (2016) 663-671.

[44] S. Ashraf, S. Naz, H. Rashmanlou, M.A. Malik, Regularity of graphs in single valued neutrosophic environment, Journal of Intelligent & Fuzzy Systems, 33 (2017) 529-542.

[45] P.D. Liu, G.L. Tang, W.L. Liu, Induced generalized interval neutrosophic Shapley hybrid operators and their application in multi-attribute decision making, Scientia Iranica, 24 (2017) 2164-2181.

[46] P.D. Liu, F. Teng, Multiple attribute group decision making methods based on some normal neutrosophic number Heronian Mean operators, Journal of Intelligent & Fuzzy Systems, 32 (2017) 2375-2391.

[47] Y.X. Ma, J.Q. Wang, J. Wang, X.H. Wu, An interval neutrosophic linguistic multi-criteria group decision-making method and its application in selecting medical treatment options, Neural Computing & Applications, 28 (2017) 2745-2765.

[48] R.X. Nie, J.Q. Wang, H.Y. Zhang, Solving Solar-Wind Power Station Location Problem Using an Extended Weighted Aggregated Sum Product Assessment (WASPAS) Technique with Interval Neutrosophic Sets, Symmetry-Basel, 9 (2017) 20.

[49] J.J. Peng, J.Q. Wang, X.H. Wu, An extension of the ELECTRE approach with multi-valued neutrosophic information, Neural Computing & Applications, 28 (2017) S1011-S1022.

[50] J. Ye, An extended TOPSIS method for multiple attribute group decision making based on single valued neutrosophic linguistic numbers, Journal of Intelligent & Fuzzy Systems, 28 (2015) 247-255.

[51] A. Elhassouny, F. Smarandache, Ieee, Neutrosophic-simplified-TOPSIS Multi-Criteria Decision-Making using combined Simplified-TOPSIS method and Neutrosophics, in: IEEE International Conference on Fuzzy Systems (FUZZ-IEEE) held as part of IEEE World Congress on Computational Intelligence (IEEE WCCI), Ieee, Vancouver, CANADA, 2016, pp. 2468-2474.

[52] S. Nadaban, S. Dzitac, Neutrosophic TOPSIS: A General View, in: 6th International Conference on Computers Communications and Control (ICCCC), Ieee, Oradea, ROMANIA, 2016, pp. 250-253.

[53] M. Abdel-Basset, M. Mohamed, F. Smarandache, A Hybrid Neutrosophic Group ANP-TOPSIS Framework for Supplier Selection Problems, Symmetry-Basel, 10 (2018) 22.

[54] J. Chen, S.Z. Zeng, C.H. Zhang, An OWA Distance-Based, Single-Valued Neutrosophic Linguistic TOPSIS Approach for Green Supplier Evaluation and Selection in Low-Carbon Supply Chains, International Journal of Environmental Research and Public Health, 15 (2018) 15.

[55] G. Xu, S. Wang, T. Yang, W. Jiang, A Neutrosophic Approach Based on TOPSIS Method to Image Segmentation, International Journal of Computers Communications & Control, 13 (2018) 1047-1061.

[56] M. Abdel-Basset, M. Saleh, A. Gamal, F. Smarandache, An approach of TOPSIS technique for developing supplier selection with group decision making under type-2 neutrosophic number, Applied Soft Computing, 77 (2019) 438-452.

[57] N.A. Nabeeh, F. Smarandache, M. Abdel-Basset, H.A. El-Ghareeb, A. Aboelfetouh, An Integrated



Neutrosophic-TOPSIS Approach and Its Application to Personnel Selection: A New Trend in Brain Processing Brain Analysis, *Ieee Access*, 7 (2019) 29734-29744.

[58] Nancy, H. Garg, A novel divergence measure and its based TOPSIS method for multi criteria decision-making under single-valued neutrosophic environment, *Journal of Intelligent & Fuzzy Systems*, 36 (2019) 101-115.

[59] S.T. Tehrim, M. Riaz, A novel extension of TOPSIS to MCGDM with bipolar neutrosophic soft topology, *Journal of Intelligent & Fuzzy Systems*, 37 (2019) 5531-5549.

[60] D. Pamucar, G. Cirovic, The selection of transport and handling resources in logistics centers using Multi-Attributive Border Approximation area Comparison (MABAC), *Expert Systems with Applications*, 42 (2015) 3016-3028.

[61] X.D. Peng, J.G. Dai, ALGORITHMS FOR INTERVAL NEUTROSOPHIC MULTIPLE ATTRIBUTE DECISION-MAKING BASED ON MABAC, SIMILARITY MEASURE, AND EDAS, *International Journal for Uncertainty Quantification*, 7 (2017) 395-421.

[62] X.D. Peng, J.G. Dai, Approaches to single-valued neutrosophic MADM based on MABAC, TOPSIS and new similarity measure with score function, *Neural Computing & Applications*, 29 (2018) 939-954.

[63] P. Wang, J. Wang, G.W. Wei, C. Wei, Y. Wei, The Multi-Attributive Border Approximation Area Comparison (MABAC) for Multiple Attribute Group Decision Making Under 2-Tuple Linguistic Neutrosophic Environment, *Informatica*, 30 (2019) 799-818.

[64] J. Wang, G.W. Wei, C. Wei, Y. Wei, MABAC method for multiple attribute group decision making under q-rung orthopair fuzzy environment, *Defence Technology*, 16 (2020) 208-216.

[65] M. Estiri, J.H. Dahooie, A.S. Vanaki, A. Banaitis, A. Binkyte-Veliene, A multi-attribute framework for the selection of high-performance work systems: the hybrid DEMATEL-MABAC model, *Economic Research-Ekonomska Istrazivanja*, 34 (2021) 970-997.

[66] M. Nedeljkovic, A. Puska, S. Doljanica, S.V. Jovanovic, P. Brzakovic, Z. Stevic, D. Marinkovic, Evaluation of rapeseed varieties using novel integrated fuzzy PIPRECIA - Fuzzy MABAC model, *Plos One*, 16 (2021) 19.

[67] M.W. Zhao, G.W. Wei, X.D. Chen, Y. Wei, Intuitionistic fuzzy MABAC method based on cumulative prospect theory for multiple attribute group decision making, *International Journal of Intelligent Systems*, 36 (2021) 6337-6359.

[68] J. Tan, Y. Liu, T. Senapati, H. Garg, Y. Rong, An extended MABAC method based on prospect theory with unknown weight information under Fermatean fuzzy environment for risk investment assessment in B&R, *Journal of Ambient Intelligence and Humanized Computing*, (2022) <https://doi.org/10.1007/s12652-12022-03769-12651>.

[69] J.J. Peng, J.Q. Wang, J. Wang, H.Y. Zhang, X.H. Chen, Simplified neutrosophic sets and their applications in multi-criteria group decision-making problems, *International Journal of Systems Science*, 47 (2016) 2342-2358.

[70] H. Wang, F. Smarandache, Y.Q. Zhang, R. Sunderraman, Single valued neutrosophic sets, *Multispace Multistruct*, (2010) 410-413.

[71] P. Majumdar, S.K. Samanta, On similarity and entropy of neutrosophic sets, *Journal of Intelligent & Fuzzy Systems*, 26 (2014) 1245-1252.

[72] Y. Wang, Using the method of maximizing deviation to make decision for multiindices, *Journal of Systems Engineering & Electronics*, 8 (1997) 21-26.

[73] E. Bolturk, A. Karasan, Prioritization of Investment Alternatives for a Hospital by Using Neutrosophic CODAS Method, *Journal of Multiple-Valued Logic and Soft Computing*, 33 (2019) 381-396.

[74] D. Stanujkic, D. Karabasevic, G. Popovic, D. Pamucar, Z. Stevic, E.K. Zavadskas, F. Smarandache, A Single-

Valued Neutrosophic Extension of the EDAS Method, *Axioms*, 10 (2021) 13.

[75] M. Keshavarz Ghorabae, M. Amiri, J.S. Sadaghiani, E.K. Zavadskas, Multi-Criteria Project Selection Using an Extended VIKOR Method with Interval Type-2 Fuzzy Sets, *International Journal of Information Technology & Decision Making*, 14 (2015) 993-1016.

[76] M. Keshavarz Ghorabae, M. Amiri, E.K. Zavadskas, J. Antucheviciene, Supplier evaluation and selection in fuzzy environments: a review of MADM approaches, *Economic Research-Ekonomska Istrazivanja*, 30 (2017) 1073-1118.

[77] G. Wei, R. Lin, J. Lu, J. Wu, C. Wei, The Generalized Dice Similarity Measures for Probabilistic Uncertain Linguistic MAGDM and Its Application to Location Planning of Electric Vehicle Charging Stations, *International Journal of Fuzzy Systems*, 24 (2022) 933-948.

[78] Z. Stevic, M. Vasiljevic, E.K. Zavadskas, S. Sremac, Z. Turskis, Selection of Carpenter Manufacturer using Fuzzy EDAS Method, *Inzinerine Ekonomika-Engineering Economics*, 29 (2018) 281-290.

[79] T.C. Chu, Facility location selection using fuzzy TOPSIS under group decisions, *International Journal of Uncertainty Fuzziness and Knowledge-Based Systems*, 10 (2002) 687-701.

[80] F. Lei, G. Wei, X. Chen, Model-based evaluation for online shopping platform with probabilistic double hierarchy linguistic CODAS method, *International Journal of Intelligent Systems*, 36 (2021) 5339-5358.

[81] Y. Li, X.D. Liu, Y. Chen, Selection of logistics center location using Axiomatic Fuzzy Set and TOPSIS methodology in logistics management, *Expert Systems with Applications*, 38 (2011) 7901-7908.

[82] D.G. Yoo, D.E. Chang, H. Jun, J.H. Kim, Optimization of pressure gauge locations for water distribution systems using entropy theory, *Environmental Monitoring and Assessment*, 184 (2012) 7309-7322.

[83] Z.L. Yang, T.X. Ouyang, X.L. Fu, X.D. Peng, A decision-making algorithm for online shopping using deep-learning-based opinion pairs mining and q-rung orthopair fuzzy interaction Heronian mean operators, *International Journal of Intelligent Systems*, 35 (2020) 783-825.

[84] S.M. Yu, Z.J. Du, X.D. Lin, H.Y. Luo, J.Q. Wang, A Stochastic Dominance-Based Approach for Hotel Selection under Probabilistic Linguistic Environment, *Mathematics*, 8 (2020).

[85] R. Zinko, P. Stolk, Z. Furner, B. Almond, A picture is worth a thousand words: how images influence information quality and information load in online reviews, *Electron. Mark.*, 30 (2020) 775-789.

[86] Y.Y. Luo, X.X. Zhang, Y. Qin, Z. Yang, Y. Liang, Tourism Attraction Selection with Sentiment Analysis of Online Reviews Based on Probabilistic Linguistic Term Sets and the IDOCRIW-COCOSO Model, *International Journal of Fuzzy Systems*, 23 (2021) 295-308.

[87] A.P. Darko, D.C. Liang, Modeling customer satisfaction through online reviews: A FlowSort group decision model under probabilistic linguistic settings, *Expert Systems with Applications*, 195 (2022) 14.

[88] Y. Qin, X.X. Wang, Z.S. Xu, Ranking Tourist Attractions through Online Reviews: A Novel Method with Intuitionistic and Hesitant Fuzzy Information Based on Sentiment Analysis, *International Journal of Fuzzy Systems*, 24 (2022) 755-777.

Received: Month Day, Year. Accepted: Month Day, Year

---

## Response to the referees

---

We are very thankful for these valuable comments given by the referees. The main changes are the following.

---

**Reviewer# 2-Q1: A paper about micro-investment compnies and strategies is presented. The paper is laborious and with some interesting example of decision making in finance withing the framework of the neutrosophic decision making. It is a professional research.**

**Answer: Many thanks for your positive comments.**

---

**Reviewer# 2: The performance evaluation of sustainable microfinance groups lending is a classical MAGDM issues. In such paper, the Hamming distances of single-valued neutrosophic sets (SVNSs) and maximizing deviation method (MDM) is used to obtain the attribute weights and the single-valued neutrosophic numbers MABAC(SVNN-MABAC) method is structured for MAGDM under SVNSs. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVNN-MABAC. My suggestion is acceptance.**

**Answer: Many thanks for your positive comments.**

---

**Reviewer# 3-Q1: Pamucar and Cirovic first proposed the MABAC method in 2015. The basic idea of MABAC method is to calculate the value of the alternative criterion function and define the distance between the criterion function and the boundary approximation region. Therefore, all alternatives can be combined into the boundary, upper approximate area or the lower approximation area. Then, rank the alternatives. In such paper, the Hamming distances of SVNSs and MDM is used to obtain the attribute decision weights and the single-valued neutrosophic MABAC(SVNN-MABAC) method is structured for MAGDM under single-valued neutrosophic sets (SVNSs). Overall this is a good approach to publish this paper in this journal, but some minor changes are needed.**

**Answer:** Many thanks for your positive comments.

---

**Reviewer# 3-Q2:** Compared with other methods, summarizing the advantages and disadvantages of the proposed method may help improve the quality of the manuscript.

**Answer:** I have revised this according to your suggestions. Please see below:

These five given models have their given advantages: (1) the SVNNTWA operator emphasis group decision influences; (2) the SVNNTWG operator emphasis individual decision influences; (3) In the SVNNT-CODAS method, the overall performance of the alternatives is measured by Euclidean distance and Hamming distance of negative ideal points, where Euclidean distance is used as the main measure for evaluation. If the Euclidean distance between two alternatives is very close, then the Hamming distance is used to compare the two alternatives. Among them, the closeness of the Euclidean distance can be determined by using the threshold parameter; (4) The SVNNT-EDAS method has required fewer computations, although it results in the same ranking of alternatives. The evaluations of alternatives in EDAS method based on distance measures from the average solutions in terms of each criterion unlike TOPSIS and VIKOR. (5) The SVNNT-MABAC method has a large amount of precious characteristic, such as: the computing results by SVNNT-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains and losses into account; it is available to combine this model with other approaches. Hence, the SVNNT-MABAC method is a good tool to derive reasonable decision making results.

---

**Reviewer# 3-Q3:** The conclusion should include the limitations of the proposed method and key directions for future research.

**Answer:** I have revised these according to your suggestions. Please see below:

According to the current research status in this field, research of evaluation methods will be continued in the following aspects in the future. (1) Consensus and consistency improvement should be investigated in group decision-making [73-79] for performance evaluation of sustainable microfinance groups lending. (2) The methods proposed in this paper is improved to consider the expression of evaluation information based on SVNNTs, such as group decision method based on probabilistic linguistic information [80, 81] and probabilistic uncertain

linguistic information [82, 83], which is also a topic worthy of future research.

---

**Reviewer# 3-Q4: Language needs revision.**

**Answer: I have improved the English quality according to your suggestions.**

---

**Reviewer# 4-Q1: In this paper, the MABAC method is built for SVN-MAGDM. The performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVN-MABAC. My suggestion is minor change: Please add the research contribution in the conclusion section.**

**Answer: Many thanks for your positive comments and I have added the research contribution in the conclusion section according to your suggestions. Please see below:**

The main contributions of this work are (1) The attribute weights are obtained by MDM method; (2) the paper constructs the SVN-MABAC method for performance evaluation of sustainable microfinance groups lending; (3) the established method is illustrated by a case study for performance evaluation of sustainable microfinance groups lending; and (4) some comparisons prove the rationality and advantages.

---

**Reviewer# 4-Q2: The abstract is not convincing, it should be refined to precisely illustrate what authors have done in this paper. The abstract must be a concise yet comprehensive reflection of what is in your paper. Remember that reader want to know: 1-what is the problem. 2- why the problem is relevant 3- wants an overview of your approach. 4-need to know the results.**

**Answer: I have revised these according to your suggestions. Please see below:**

**Abstract:** As an important supplement to my country's financial institutions, micro-loan companies serve "agriculture, rural areas and farmers", small and micro enterprises, and individuals, to a certain extent, alleviating the financing difficulties of such groups and regulating private finance. However, micro-loan companies only lend but do not deposit. In the process of lending, due to inadequate risk management, the risk problem has become increasingly prominent. With the continuous growth of the loan amount of rural credit and the continuous increase of microfinance groups lending customers, it faces certain problems in its risk management, which increases the risks of the company in all aspects. The performance evaluation of sustainable

microfinance groups lending is a classical MAGDM issues. In such paper, the Hamming distances of single-valued neutrosophic sets (SVNSs) and maximizing deviation method (MDM) is used to obtain the attribute weights and the single-valued neutrosophic numbers MABAC(SVNN-MABAC) method is structured for MAGDM under SVNSs. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to proof the SVNN-MABAC.

---

**Reviewer# 4-Q3: In the Introduction part, the new features of the proposed method and the main advantages of the results over others should be clearly described.**

**Answer: I have revised these according to your suggestions. Please see below:**

(3) The main advantages of the SVNN-MABAC method are given as follows: the computing results by SVNN-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains and losses into account; it is available to combine this model with other approaches. Hence, the SVNN-MABAC method is a good tool to derive reasonable decision-making results.

---

**Reviewer# 4-Q4: An introduction should clearly highlight the motivation, problem statement, the objective of the paper, gap in the existing research and the novelty of the conducted research.**

**Answer: I have revised these according to your suggestions. Please see below:**

There are three shortcomings in disposing of the MAGDM problems under SVNNs environment that to form our incentives in the following:

(1) The existing decision methods have complex computation degree[38-49]. How to investigate the decision methods consider the relatively simpler computation degree is an interesting and hot topic. For this reason, the first incentive of this paper is to build the new relatively simpler decision methods.

(2) The existing weight methods just consider completely known weight information[32-37]. How to investigate the weight consider completely unknown weight is an interesting and hot topic. For this reason, the second incentive of this paper is to design the new weight method, which can deal with completely unknown weight.

(3) The timely innovation of group lending technology of microfinance is important for

promoting the innovation of financial support for agricultural products in the implementation of China's rural revitalization strategy [60-65]. It is of practical value and theoretical significance to promote the innovation of financial support for agricultural products in the implementation of China's rural revitalization strategy and to bridge the theoretical controversy of microcredit loan technology. The performance evaluation of sustainable microfinance groups lending in Chinese is still in a blank state. Therefore, it is urgent for researchers in related disciplines to conduct exploratory research in this field to enrich the research content of performance evaluation of sustainable microfinance groups lending in my country. The performance evaluation of sustainable microfinance groups lending is a classical MAGDM issues. Thus, the third incentive of this paper is to build new decision methods for performance evaluation of sustainable microfinance groups lending.

On this basis, combined with the characteristics of performance evaluation of sustainable microfinance groups lending, a new MAGDM method for performance evaluation of sustainable microfinance groups lending in SVNNs environment is proposed. Specific research points are listed as follows:

(1) In this paper, the SVNN-MABAC method is built based on the MABAC [66] and SVNNs with completely unknown weight information. The SVNN-MABAC investigate the decision methods consider the distances-based measures degree.

(2) For deriving the completely known weight of the attribute, an optimization model is built on the MDM method, by which the attribute weights can be decided. Then, the optimal alternative is chosen through calculating the maximizing deviation among different alternatives. Then, combine the traditional MABAC model with SVNNs information, the SVNN-MABAC method is established and the computing steps for MAGDM are built.

(3) The main advantages of the SVNN-MABAC method are given as follows: the computing results by SVNN-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains and losses into account; it is available to combine this model with other approaches. Hence, the SVNN-MABAC method is a good tool to derive reasonable decision-making results.

(4) Finally, a numerical example for performance evaluation of sustainable microfinance groups lending has been given and some comparisons is used to illustrate advantages of SVNN-MABAC. This paper mainly provides method guidance and technical support for the realization of SVNN-

MABAC. This has far-reaching significance for the decision-making of sustainable microfinance groups lending in the public sector, infrastructure construction and even national security and stability.

---

**Reviewer# 4-Q5: This application topic has not received much attention in the literature. However, the study, literature review and presentation require substantial improvement in several respects.**

**Answer: I have revised these according to your suggestions. Please see below:**

(3) The timely innovation of group lending technology of microfinance is important for promoting the innovation of financial support for agricultural products in the implementation of China's rural revitalization strategy [60-65]. It is of practical value and theoretical significance to promote the innovation of financial support for agricultural products in the implementation of China's rural revitalization strategy and to bridge the theoretical controversy of microcredit loan technology. The performance evaluation of sustainable microfinance groups lending in Chinese is still in a blank state. Therefore, it is urgent for researchers in related disciplines to conduct exploratory research in this field to enrich the research content of performance evaluation of sustainable microfinance groups lending in my country. The performance evaluation of sustainable microfinance groups lending is a classical MAGDM issues. Thus, the third incentive of this paper is to build new decision methods for performance evaluation of sustainable microfinance groups lending.

---

**Reviewer# 4-Q6: Result and Discussion section is inadequate. Need more attention and better explanation.**

**Answer: I have revised these according to your suggestions. Please see below:**

From Table 7, obviously, the best enterprise given is  $PP_2$  in the five given methods, and the worst selection is  $PP_3$  in most cases. In other words, the order of these five methods have light difference. Different decision methods may effectively solve the MAGDM problem from different research decision angles. These five given models have their given advantages: (1) the SVNNWA operator emphasis group decision influences; (2) the SVNNWG operator emphasis individual



decision influences; (3) In the SVN-CODAS method, the overall performance of the alternatives is measured by Euclidean distance and Hamming distance of negative ideal points, where Euclidean distance is used as the main measure for evaluation. If the Euclidean distance between two alternatives is very close, then the Hamming distance is used to compare the two alternatives. Among them, the closeness of the Euclidean distance can be determined by using the threshold parameter; (4) The SVN-EDAS method has required fewer computations, although it results in the same ranking of alternatives. The evaluations of alternatives in EDAS method based on distance measures from the average solutions in terms of each criterion unlike TOPSIS and VIKOR. (5) The SVN-MABAC method has a large amount of precious characteristic, such as: the computing results by SVN-MABAC method are stable; the calculating equations are simple; it takes the latent values of gains and losses into account; it is available to combine this model with other approaches. Hence, the SVN-MABAC method is a good tool to derive reasonable decision making results.

---

**Reviewer# 4-Q7: I suggest extending the conclusions section to focus on the results you get, the method you propose, and their significance.**

**Answer: I have revised these according to your suggestions. Please see below:**

In recent years, the development of Internet finance has shown an unprecedented prosperous trend, which is the result of the rapid development of Internet information technology and cloud technology. Under this background, there are endless cases of innovation and entrepreneurship in the domestic Internet finance field, especially the development of Internet wealth management products. Especially quickly. In 2014, Alibaba Finance launched the "Yue Bao" service for the first time, mainly providing Alipay wealth management services. This product is a wealth management fund product jointly launched by Alipay and Tianhong Fund. Money market financial instruments with high security and stability, such as certificates of deposit. Once the Yu'e Bao product was launched, it aroused strong reactions in the financial investment market. It is known as a "wealth management artifact" due to its low threshold and fast receipt of income. Under this wave, other Internet financial companies have followed closely and launched various wealth management products, such as Baidu's "Baifa", Suning's "Change Money", Tencent's "Wealth Management", etc. Financial markets are showing unprecedented prosperity. The performance evaluation of sustainable microfinance groups lending is the MAGDM. In this given paper, the MABAC method is built for

SVNN-MAGDM. First, the Hamming distances of SVNNS and MDM is employed to obtain the decision weights and the SVNN-MABAC method is structured for MAGDM under SVNNS. Finally, an example about performance evaluation of sustainable microfinance groups lending and some comparative decision analysis are given to prove the SVNN-MABAC. The main contributions of this work are (1) The attribute weights are obtained by MDM method; (2) the paper constructs the SVNN-MABAC method for performance evaluation of sustainable microfinance groups lending; (3) the established method is illustrated by a case study for performance evaluation of sustainable microfinance groups lending; and (4) some comparisons prove the rationality and advantages.

---

**Reviewer# 4-Q8: Expand literature review by citing related work.**

**Generalization of Maximizing Deviation and TOPSIS Method for MADM in Simplified Neutrosophic Hesitant Fuzzy Environment. Symmetry, 11(8) (2019), 1058**

**Decision-making with bipolar neutrosophic TOPSIS and bipolar neutrosophic ELECTRE-I, Axioms 2018, 7, 33**

**Extended CODAS method for multi-attribute group decision-making based on 2-tuple linguistic Fermatean fuzzy Hamacher aggregation operators. Granul. Comput. (2022). <https://doi.org/10.1007/s41066-022-00332-3>**

**Assessment of Hydropower Plants in Pakistan: Muirhead Mean-Based 2-Tuple Linguistic T-spherical Fuzzy Model Combining SWARA with COPRAS. Arab J Sci Eng (2022). <https://doi.org/10.1007/s13369-022-07081-0>**

**2-Tuple Linguistic Fermatean Fuzzy Decision-Making Method Based on COCOSO with CRITIC for Drip Irrigation System Analysis. Journal of Computational and Cognitive Engineering. <https://doi.org/10.47852/bonviewJCCE2202356>**

**Answer: I have cited these papers according to your suggestions. Please see below:**

The MADM is a kind of very complex optimization decision-making problem, which often occurs in the field of decision engineering, economics, military, and public management[1-5].

[1] M. Akram, S. Naz, F. Smarandache, Generalization of Maximizing Deviation and TOPSIS Method for MADM in Simplified Neutrosophic Hesitant Fuzzy Environment, Symmetry-Basel, 11 (2019).

- [2] M. Akram, Shumaiza, F. Smarandache, Decision-Making with Bipolar Neutrosophic TOPSIS and Bipolar Neutrosophic ELECTRE-I, *Axioms*, 7 (2018).
- [3] M. Akram, Z. Niaz, F. Feng, Extended CODAS method for multi-attribute group decision-making based on 2-tuple linguistic Fermatean fuzzy Hamacher aggregation operators, *Granular Computing*, (2022) <https://doi.org/10.1007/s41066-41022-00332-41063>.
- [4] M. Akram, S. Naz, F. Feng, A. Shafiq, Assessment of hydropower plants in Pakistan: Muirhead mean-based 2-tuple linguistic t-spherical fuzzy model combining SWARA with COPRAS, *Arabian Journal for Science Engineering*, (2022) <https://doi.org/10.1007/s13369-13022-07081-13360>.
- [5] M. Akram, Z. Niaz, 2-Tuple linguistic Fermatean fuzzy decision-making method based on COCOSO with CRITIC for drip irrigation system analysis, *Journal of Computational Cognitive Engineering*, (2022) <https://doi.org/10.47852/bonviewJCCE2202356>.
-